

Epson PowerLite L210W dataprojektori 4500 ANSI lumenia 3LCD WXGA (1280x800) Valkoinen

Tuotemerkki : Epson

Tuoteperhe: PowerLite

Tuotekoodi: V11HA70080

Tuotteen nimi : L210W



Epson PowerLite L210W. Projektorin kirkkaus: 4500 ANSI lumenia, Projektioteknologia: 3LCD, Projektorin oletusresoluutio: WXGA (1280x800). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 30000 h. Tarkennus: Ohje, Polttovälialue: 18.2 - 29.1 mm, Aukkoalue (F-F): 1,51 - 1,77. Sarjaliitännän tyyppi: RS-232C. Melutaso: 37 dB, Melutaso (taloudellinen tila): 27 dB

Projector		Ports & interfaces	
Smart projector *	✗	DVI port *	✗
Screen size compatibility *	762 - 7620 mm (30 - 300")	Network	
Projector brightness *	4500 ANSI lumens	Smart TV *	✗
Projection technology *	3LCD	Ethernet LAN *	✓
Projector native resolution *	WXGA (1280x800)	Wi-Fi *	✗
Contrast ratio (typical) *	2500000:1	Storage	
Native aspect ratio *	16:10	Card reader integrated *	✗
Keystone correction, horizontal	-30 - 30°	Features	
Keystone correction, vertical	-30 - 30°	Interactive *	✗
Matrix size	1.5 cm (0.59")	Noise level (economic mode)	27 dB
Light source		Noise level *	37 dB
Light source type *	Laser	Multimedia	
Service life of light source *	20000 h	Built-in speaker(s) *	✓
Service life of light source (economic mode)	30000 h	RMS rated power	16 W
Lens system		Number of built-in speakers	1
Focus *	Manual	Design	
Focal length range	18.2 - 29.1 mm	Market positioning *	Business
Aperture range (F-F)	1.51 - 1.77	Product colour *	White
Zoom capability	✓	Display	
Zoom type	Manual	Built-in display *	✗
Zoom ratio	1.16:1	Power	
Throw ratio	1.41 - 2.26	Power source *	AC
Video		Power consumption (typical) *	201 W
Analog signal format system *	Not supported	Power consumption (max)	260 W
Full HD *	✓	Power consumption (economy mode)	199 W
3D *	✗	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50/60 Hz
USB 2.0 ports quantity	2	Operational conditions	
USB 2.0 Type-A ports quantity	1	Operating temperature (T-T)	0 - 40 °C
USB 2.0 Type-B ports quantity	1		
Serial interface type *	RS-232C		
VGA (D-Sub) ports quantity *	2		

Ports & interfaces		Weight & dimensions	
HDMI ports quantity *	2	Width	325 mm
		Depth	299 mm
		Height	90 mm
		Weight *	4.2 kg
Packaging content			
Remote control included *			✓
Batteries included			✓
Cables included			AC, HDMI



8715946715476

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date