## Epson EB-L265F data projector 4600 ANSI lumens 3LCD 1080p (1920x1080) 3D Black

**Brand :** Epson **Product code:** V11HA72180

**Product name:** EB-L265F







Projector		Network	
Smart projector * Screen size compatibility * Projector brightness *	× 787.4 - 7874 mm (31 - 310") 4600 ANSI lumens	Smart TV * Ethernet LAN * Wi-Fi *	net LAN *
Projection technology * Projector native resolution *	3LCD 1080p (1920x1080)	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Contrast ratio (typical) * Native aspect ratio *	2500000:1 16:9	Storage	
Number of colours	1.07 billion colours	Card reader integrated *	x
Projector brightness (economic mode)	3200 ANSI lumens	Features	
Keystone correction, horizontal Keystone correction, vertical Matrix size	-30 - 30° -30 - 30° 1.57 cm (0.62")	Interactive * Noise level (economic mode) HDCP	X 27 dB ✓
Light source		Noise level *  Multimedia	37 dB
Light source type * Service life of light source * Service life of light source (economic mode)	Laser 20000 h 30000 h	Built-in speaker(s) * RMS rated power  Design	<b>✓</b> 16 W
Lens system		Market positioning *	Presentation
Focus * Focal length range Aperture range (F-F) Zoom capability	Manual 18.2 - 29.1 mm 1.51 - 1.77 ✓	Product colour * Placement Cable lock slot Cable lock slot type	Black Ceiling, Floor, Wall  Kensington
Zoom type	Manual	Display	
Zoom ratio Throw ratio	1:1.62 1,32 - 2,12:1	Built-in display *	×
Video		Power	
Analog signal format system * Full HD * 3D *	Not supported  ✓	Power source * Power consumption (typical) * Power consumption (economy mode)	AC 199 W 144 W
Video colour modes	Blackboard, Cinema, Dynamic, Multi-projection, Presentation, sRGB	AC input voltage AC input frequency	220 - 240 V 50/60 Hz
Ports & interfaces		Ac input inequency	30,00 112
Service port type	USB Type-B		

orts & interfaces		Operational conditions		
USB 2.0 ports quantity	1	Storage temperature (T-T)	-10 - 60 °C	
Headphone outputs	3	Operating relative humidity (H-H)	20 - 80%	
Serial interface type *	RS-232C	Storage relative humidity (H-H)	10 - 90%	
VGA (D-Sub) ports quantity *	3	Weight & dimensions		
IDMI ports quantity *	2	Weight *	4.2 kg	
Composite video in *	1	3	4.2 Ng	
DVI port *	×	Packaging content	Packaging content	
		Remote control included *	✓	
		Batteries included	✓	
		Cables included	AC, HDMI	



8715946715490

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.