EPSON'

Epson EB-775F dataprojektori Lähietäisyysprojektori 4100 ANSI lumenia 3LCD 1080p (1920x1080) musta

Tuotemerkki : Epson Tuotekoodi: V11HA83180

Tuotteen nimi: EB-775F

Epson EB-775F. Projektorin kirkkaus: 4100 ANSI lumenia, Projektioteknologia: 3LCD, Projektorin oletusresoluutio: 1080p (1920x1080). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h. Tarkennus: Ohje, Zoomaussuhde: 1.35:1. Tuetut videomoodit: 1080p. Sarjaliitännän tyyppi: RS-232C





Supported aspect ratios 16:9, 21:9 Card reader integrated * X Screen size compatibility * 1244.6 - 3810 mm (49 - 150") Multimedia Projector brightness * 4100 ANSI lumens 3 LCD Built-in speaker(s) * ✓ Projector native resolution * 1080p (1920x1080) RMS rated power 16 W Contrast ratio (typical) * 2500000:1 Number of built-in speakers 1 Native aspect ratio * 16:9 Design Light source				
Screen size compatibility 1244.6 - 3810 mm (49 - 150") Multimedia Projector brightness 4100 ANSI lumens Projector brightness 3 LCD Built-in speaker(s)	Projector		Storage	
Projector brightness* 4100 ANSI lumens Brojector brightness* 4100 ANSI lumens Brojection technology* 3LCD Built-in speaker(s)* ✓ Projector native resolution* 1080p (1920x1080) RMS rated power 16 W Contrast ratio (typical)* 2500000:1 Number of built-in speakers 1 Native aspect ratio* 16:9 Design Light source type * Laser Product type * Ultra short throw projector Black Service life of light source * 20000 h Product colour* Black Ultra short throw projector Service life of light source * 20000 h Product colour* Black Ultra short throw projector Service life of light source * 20000 h Product colour* Black Ultra short throw projector Service life of light source * 20000 h Product colour* Black Ultra short throw projector Service life of light source * 20000 h Product colour* Black Ultra short throw projector Product colour* Black Product colour* Black Ultra short throw projector Service life of light source * 20000 h Product colour* Black Ultra short throw projector Product colour* Black Product Colour* Black Product Colour* Black Ultra short throw projector Service life of light source * 20000 h Product Colour* Black Product Colour* AC Colour* Power Consumption (typical)* 263 W Power Consumption	Screen size compatibility * 1 Projector brightness * 4	1244.6 - 3810 mm (49 - 150") 4100 ANSI lumens	Card reader integrated *	X
Projection technology * 3LCD Built-in speaker(s) * ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓			Multimedia	
Projector native resolution * 1080p (1920x1080) RMS rated power 16 W Contrast ratio (typical) * 2500000:1 Number of built-in speakers 1 Native aspect ratio * 16:9 Design Light source			Built-in speaker(s) *	✓
Contrast ratio (typical) * 2500000:1 Number of built-in speakers 1 Native aspect ratio * 16:9 Design Light source Light source type * Laser Light folight source * 20000 h Product type * Ultra short throw projector Black Lens system Focus * Manual Zoom capability Focus * Manual Zoom ratio 1.35:1 Power Zoom ratio 1.35:1 Power source * AC Power consumption (typical) * 263 W Supported video modes 1080p Ports & interfaces USB 2.0 ports quantity USB 2.0 Type-B ports quantity 1 Operating temperature (T-T) Serial interface type * RS-232C Width Ord VGA (D-Sub) ports quantity * 2 Depth 395 mm HolMI ports quantity * 3 Height & dimensions For the first of the	,		RMS rated power	16 W
Light source Light source type * Laser Product type * Ultra short throw projector Service life of light source * 20000 h Product colour * Black Lens system Focus * Manual Built-in display * X Zoom capability	Contrast ratio (typical) *	·	Number of built-in speakers	1
Light source type * Laser	Native aspect ratio *	16:9	Design	
Service life of light source * 20000 h Product colour * Black Lens system Focus * Manual Built-in display * X Zoom capability	Light source		Market positioning *	Presentation
Lens system Focus * Manual Built-in display * X Zoom capability	Light source type *	Laser	Product type *	Ultra short throw projector
Focus * Manual Built-in display * X Zoom capability	Service life of light source *	20000 h	Product colour *	Black
Zoom capability Zoom ratio 1.35:1 Power Surrce* Power consumption (typical)* 263 W Full HD* Supported video modes 1080p AC input voltage AC input voltage AC input frequency So/60 Hz Porest & interfaces USB 2.0 ports quantity 1 USB 2.0 Type-B ports quantity 1 Serial interface spee AU input frequency So/60 Hz Departing temperature (T-T) Storage temperature (T-T) -10 - 60 °C Audio (L/R) out 1 Weight & dimensions Serial interface type* RS-232C Width 395 mm HDMI ports quantity* 3 Height Height Height 133 mm DVI port* X AC (power) in Network Remote control included* Full HDM AC (ables included AC (ables included) AC (ables included AC (ables included) AC (ables included AC (ables included) AC (ables included) AC (ables included AC (ables included) AC (ables included) AC (ables included AC (ables included) AC (ables included) AC (ables included AC (ables included) AC (ables included) AC (ables included) AC (ables included AC (ables included) AC	Lens system		Display	
Zoom ratio 1.35:1 Power source * AC Video Power consumption (typical) * 263 W Full HD * ✓ Power consumption (standby) * 0.5 W Supported video modes 1080p AC input voltage 100 - 240 V AC input voltage 100 - 240 V AC input frequency 50/60 Hz Ports & interfaces USB 2.0 ports quantity 1 Operational conditions USB 2.0 Type-B ports quantity 1 Operating temperature (T-T) 0 - 40 °C Audio (L/R) in * 2 Storage temperature (T-T) -10 - 60 °C Audio (L/R) out 1 Weight & dimensions Serial interface type * RS-232C Width 356 mm VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 3 Height 133 mm DVI port * X Weight * 5.9 kg AC (power) in ✓ Packaging content Network X Batteries included ✓ Ethernet LAN * ✓ Batteries included AC Wi-Fi * ✓	Focus *	Manual	Built-in display *	×
Video Power source* AC Full HD * 263 W Full HD * 263 W Supported video modes 1080p AC input voltage 100 - 240 V AC input frequency 50/60 Hz Operational conditions USB 2.0 ports quantity 1 Operating temperature (T-T) 0 - 40 °C Audio (L/R) out 1 Weight & dimensions Serial interface type * RS-232C Width 356 mm VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 2 Depth 335 mm HDMI ports quantity * 2 Depth 133 mm DVI port * X Weight * 5.9 kg AC (power) in Y Packaging content Network Packaging content	Zoom capability	✓	Power	
Full HD *	Zoom ratio	1.35:1	Power source *	AC
Supported video modes 1080p Ports & interfaces USB 2.0 ports quantity 1 Audio (L/R) in * 2 Audio (L/R) out 1 Serial interface type * RS-232C WGA (D-Sub) ports quantity * 2 HDMI ports quantity * 3 DVI port * X AC input voltage 50/60 Hz Departional conditions Weight & dimensions Weight & dimensions Weight & dimensions Serial interface type * RS-232C Width 356 mm VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 3 Height 133 mm DVI port * X AC (power) in	Video		Power consumption (typical) *	263 W
Ports & interfaces USB 2.0 ports quantity USB 2.0 Type-B ports quantity Audio (L/R) in * 2 Audio (L/R) out Serial interface type * VGA (D-Sub) ports quantity * Depth HDMI ports quantity * DVI port * AC (power) in Network Ethernet LAN * Ethernet LAN (RJ-45) ports 1000 Depth AC input frequency Depta	Full HD *	✓	• • • • • • • • • • • • • • • • • • • •	
Ports & interfaces USB 2.0 ports quantity 1 Operational conditions USB 2.0 Type-B ports quantity 1 Operating temperature (T-T) 0 - 40 °C Audio (L/R) in * 2 Storage temperature (T-T) -10 - 60 °C Audio (L/R) out 1 Weight & dimensions Serial interface type * RS-232C Width 356 mm VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 3 Height 133 mm DVI port * X Weight * 5.9 kg AC (power) in ✓ Packaging content Network Remote control included * ✓ Ethernet LAN * ✓ Batteries included ✓ Ethernet LAN (RJ-45) ports 1 Cables included AC Wi-Fi * ✓ Quick start guide ✓	Supported video modes	1080p	· -	
USB 2.0 ports quantity USB 2.0 Type-B ports quantity Audio (L/R) in * Audio (L/R) out Serial interface type * VGA (D-Sub) ports quantity * BUSIN TYPE SUBJECT SU	Ports & interfaces			50/60 HZ
Audio (L/R) in * Audio (L/R) out Storage temperature (T-T) Audio (L/R) out Serial interface type * RS-232C Width Septh S	USB 2.0 ports quantity	1		
Audio (L/R) in * 2 Audio (L/R) out 1 Weight & dimensions Serial interface type * RS-232C Width 356 mm VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 3 Height 133 mm DVI port * * Weight * 5.9 kg AC (power) in	USB 2.0 Type-B ports quantity	1		
Serial interface type * RS-232C Width 356 mm VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 3 Height 133 mm DVI port * Weight * 5.9 kg AC (power) in	Audio (L/R) in *	2		-10 - 60 °C
VGA (D-Sub) ports quantity * 2 Depth 395 mm HDMI ports quantity * 3 Weight * 5.9 kg AC (power) in Network Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Width 355 mm Height 133 mm 5.9 kg Packaging content Remote control included * Batteries included Cables included AC Quick start guide	Audio (L/R) out	=	-	
HDMI ports quantity * 3 Height 133 mm DVI port * Weight * 5.9 kg AC (power) in Packaging content Remote control included * Ethernet LAN * Batteries included Ethernet LAN (RJ-45) ports 1 Cables included AC Wi-Fi * Quick start guide				
DVI port *			•	
AC (power) in Packaging content Remote control included * Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Cables included AC Wi-Fi * Quick start guide		_	-	===
Tackaging content Network Remote control included * ✓ Ethernet LAN * ✓ Batteries included ✓ Ethernet LAN (RJ-45) ports 1 Cables included AC Wi-Fi * ✓ Quick start guide ✓	·		,	J.3 ky
Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Cables included AC Wi-Fi * Quick start guide	·	•		
Ethernet LAN (RJ-45) ports 1 Cables included AC Wi-Fi * ✓ Quick start guide ✓				
Wi-Fi * Quick start guide ✓				
•	- ·	1		
Manual ✓ Manual ✓		•		
	MIracast	•	Manuai	∀

Technical details		
Warranty period	5 year(s)	
Logistics data		
Quantity per pack	1 pc(s)	



8715946715711

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.