
Epson EB-L570U dataprojektori 5200 ANSI lumenia 3LCD WUXGA (1920x1200) musta, Valkoinen

Tuotemerkki : Epson Tuotekoodi: V11HA98080

Tuotteen nimi: EB-L570U







Projector		Network	
Screen size compatibility * Projection distance	1270 - 12700 mm (50 - 500") 1.44 - 23.84 m 1.4 - 14.8 m 2.4 - 23.8 m 5200 ANSI lumens 3LCD WUXGA (1920x1200) 2500000:1 16:10 1.07 billion colours -30 - 30° -30 - 30° 1.7 cm (0.67")	Ethernet LAN * Wi-Fi *	×
Projection distance (wide)		Storage	
Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Keystone correction, horizontal Keystone correction, vertical		Card reader integrated *	×
		Features	
		Interactive * Noise level (economic mode) Noise level * High Dynamic Range (HDR) supported High Dynamic Range (HDR) technology	X 23 dB 31 dB ✓ High Dynamic Range 10 (HDR10)
Light source		Multimedia	
Light source type * Service life of light source * Service life of light source	Laser 20000 h 30000 h	Built-in speaker(s) * RMS rated power Design	✓ 10 W
(economic mode)		Market positioning *	Business
Lens system Focus *	Manual	Product colour *	Black, White
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range	Manual 20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50%	Power Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency	AC 201 W 2 W 260 W 199 W 50/60 Hz
	Not gunnarted	AC adapter output voltage	100 - 240 V
Analog signal format system * Full HD *	Not supported	Operational conditions	
3D *	×	Storage temperature (T-T) Operating relative humidity (H-H)	-10 - 60 °C 20 - 80%
Ports & interfaces		Storage relative humidity (H-H)	10 - 90%
HDBaseT port USB 2.0 ports quantity USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity	2 1 1	Weight & dimensions Width Depth	440 mm 304 mm

Ports & interfaces		Weight & dimensions		
Serial interface type *	RS-232C	Height	122 mm	
HDMI ports quantity *	3	Weight *	8.3 kg	
DVI port *	×	Packaging content		
		Remote control included *	✓	
		Batteries included	✓	
		Cables included	AC	



8715946714912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.