

## Lenovo 4XC7A76525 network card Internal Fiber 32000 Mbit/s

Brand : Lenovo

Product code: 4XC7A76525

Product name : 4XC7A76525

ThinkSystem Emulex LPe35002 32Gb 2-port PCIe Fibre Channel Adapter V2

Lenovo 4XC7A76525 network card Internal Fiber 32000 Mbit/s:

The next generation Emulex 32 Gb LPe35000/LPe35002 1-port and 2-port Fibre Channel host bus adapters for ThinkSystem servers are an ideal solution when requiring high-speed data transfer in storage connectivity for virtualized environments, data backup, and mission-critical applications.

This product guide describes the Emulex HBAs and provides essential pre-sales information to understand the products, their key features and specifications, and compatibility. This guide is intended for technical specialists, sales specialists, sales engineers, and IT architects who want to learn more about the adapters and consider their use in IT solutions.

Lenovo 4XC7A76525. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Fiber. Maximum data transfer rate: 32000 Mbit/s. Product colour: Black, Green, Stainless steel

| Ports & interfaces   |   | Design                             |  |
|--|---|------------------------------------|--|
| Connectivity technology *<br>Host interface *<br>Interface *<br>Fiber ports quantity | Wired<br>PCI Express<br>Fiber<br>2  | Compatible products                | SR630 (7X01/7X02), SR650<br>(7X05/7X06), SR635 (7Y98 / 7Y99),<br>SR655 (7Y00 / 7Z01), SR850<br>(7X18/7X19), SR860 (7X69/7X70),<br>SR950 (7X11/12/13) |
| Fiber optic connector  | SFP+  | System requirements                |  |
| PCI version  | 4.0   |                                    | Red Hat Enterprise Linux 7.6, Red  |
| Network  | ork   |                                    | Hat Enterprise Linux 7.7, Red Hat  |
| Maximum data transfer rate *   | 32000 Mbit/s  | Compatible operating systems       | Enterprise Linux 8.0, VMware<br>vSphere Hypervisor (ESXi) 6.7 U1,<br>VMware vSphere Hypervisor (ESXi)<br>6.7 U2, VMware vSphere Hypervisor           |
| Design   | -   |                                    |  |
| Component for *  | Server  |                                    | (ESXi) 6.7 U3  |
| Product colour<br>Internal *   | Black, Green, Stainless steel   | Server operating systems supported | SUSE Linux Enterprise Server 12,<br>Windows Server 2016, Windows<br>Server 2019  |
| Hot-Plug support   | ✓   | Operational conditions             |  |
| Certification  | AS/NZS CISPR22:2009+A1, Class A,<br>Australian EMC Framework (RCM),<br>China RoHS compliant, cUR<br>recognized to CSA 22.2, No.<br>60950-1-07, EN55022:2010, Class<br>A, EN55024:2010, EN55032:2012,<br>EU (CE Mark), FCC Rules, Part 15,<br>Class A, Industry Canada, ICES-003,<br>Class A, Japan VCCI, Class A, Korea<br>MSIP, Class A, RoHS Compliant<br>(Directive 2011/65/EU), TUV<br>certified to<br>EN60950-1+A11+A1+A12+A2,<br>Taiwan BSMI, Class A, UL<br>recognized to UL60950-1 2nd<br>Edition | Operating temperature (T-T)        | 0 - 55 °C  |
|  |   | Storage temperature (T-T)          | -20 - 85 °C  |
|  |   | Operating relative humidity (H-H)  | 5 - 95%  |
|  |   | 1 5 , , ,                          | 5 55 %   |
|  |   | Weight & dimensions                |  |
|  |   | Width                              | 69 mm  |
|  |   | Depth                              | 168 mm   |
|  |   | Logistics data                     |  |
|  |   | Harmonized System (HS) code        | 85176990   |
|  |   | Other features                     |  |
|  |   | Minimum operating temperature      | 0 °C   |
|  |   | Maximum operating temperature      | 55 °C  |







889488586714

0889488586714

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.