Canon

Canon imagePROGRAF TA-20 large format printer Wi-Fi Inkjet Colour 2400 x 1200 DPI A1 (594 x 841 mm) Ethernet LAN

Brand : Canon

Product family: imagePROGRAF

Product code: 3659C003

Product name : TA-20

5 colors, 24"/610mm, 2400 x 1200 dpi, 15360 nozzles, 2GB, 37kg
Canon imagePROGRAF TA-20. Print technology: Inkjet, Maximum resolution: 2400 x 1200 DPI, Page description languages: HP-GL/2, HP-RTL, JPEG. Maximum print size: A1 (594 x 841 mm), ISO A-series sizes (A0...A9): A1, Borderless printing media sizes: A1. Ethernet interface type: Gigabit Ethernet, USB connector: USB Type-A, Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Black, Grey, Display: LED, Display diagonal: 7.62 cm (3"). Power consumption (standby): 3.6 W, Power consumption (typical): 52 W, Power consumption (off): 0.3 W

Printing

Print technology *	Inkjet
Colour *	✔
Maximum resolution *	2400 x 1200 DPI
Number of print cartridges *	6
Page description languages *	HP-GL/2, HP-RTL, JPEG
Printing colours *	Black, Cyan, Magenta, Matte black, Yellow
Borderless printing	✔

Copying

Copying *	✘

Scanning

Scanning *	✘

Input & output capacity

Total number of input trays	1

Paper handling

Maximum print size *	A1 (594 x 841 mm)
ISO A-series sizes (A0...A9)	A1
Borderless printing media sizes	A1
Cut sheets *	✔
Media thickness	0.07 mm
Maximum roll length	18 m
Maximum roll diameter	15 cm
Print margin cut-sheet	210 - 431.8 mm
Media width (rolls)	203.2 - 610 mm
Borderless printing width	24"
Roll paper	✔

Ports & interfaces

Wi-Fi *	✔
Ethernet interface type	Gigabit Ethernet
Ethernet LAN *	✔
USB port *	✔
USB connector	USB Type-A
USB 2.0 ports quantity	1
Ethernet LAN data rates	10,100,1000 Mbit/s
RJ-45 ports quantity	1

Performance

Product colour *	Black, Grey
Built-in display *	✔

Performance

Display	LED
Display diagonal	7.62 cm (3")
Control type	Touch
Internal memory	2048 MB
Sound pressure level (printing)	42 dB
Certification	CE mark, EAC, TUV, CB

Power

Power consumption (standby)	3.6 W
Power consumption (typical)	52 W
Power consumption (off)	0.3 W

Operational conditions

Operating relative humidity (H-H)	10 - 80%
Storage temperature (T-T)	15 - 30 °C

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks

Weight & dimensions

Width	982 mm
Depth	748 mm
Height	438 mm
Weight	37 kg

Packaging data

Package width	1147 mm
Package depth	874 mm
Package height	542 mm
Package weight	49 kg
Cartridge(s) included	✔
Drivers included	✔
Manual	✔
Quick start guide	✔

Other features

Noise level (ready)	35 dB
Touchscreen	✔

Logistics data

Harmonized System (HS) code	84433210

4549292141962