

## Xerox B305, A4, 38 s/min, langaton, kaksipuolinen kopiointi/tulostus/skannaus, PS3 PCL5e/6 , 2 alustaa, 350 arkkia

**Tuotemerkki :** Xerox

**Tuotekoodi:** B305V\_DNI

**Tuotteen nimi :** Xerox B305, A4, 38 s/min, langaton, kaksipuolinen kopiointi/tulostus/skannaus, PS3 PCL5e/6 , 2 alustaa, 350 arkkia

Xerox B305, A4, 38 s/min, langaton, kaksipuolinen kopiointi/tulostus/skannaus, PS3 PCL5e/6 , 2 alustaa, 350 arkkia. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 2400 x 2400 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 38 ppm. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskanuus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Kaksipuolinen toiminto: Kopiointi, Tulosta. Suurin ISO A-luokan paperikoko: A4. Wi-Fi. Suoratulostus. Tuotteen väri: Sininen, Valkoinen



Printing		Paper handling	
Duplex printing mode	Auto	Custom media length	148 - 356 mm
Print resolution black	600 x 600 DPI	Paper tray media weight	60 - 120 g/m <sup>2</sup>
Print technology *	Laser	Multi-Purpose Tray media weight	60 - 217 g/m <sup>2</sup>
Printing *	Mono printing	Auto Document Feeder (ADF) media weight	60 - 90 g/m <sup>2</sup>
Duplex printing *	✓	Duplex media weight	60 - 90 g/m <sup>2</sup>
Maximum resolution *	2400 x 2400 DPI	<b>Ports &amp; interfaces</b>	
Print speed (black, normal quality, A4/US Letter) *	38 ppm	Direct printing *	✓
Print speed (colour, normal quality, A4/US Letter)	38 ppm	USB port	✓
Duplex print speed (black, normal quality, A4/US Letter)	17 ppm	USB connector	USB Type-B
Duplex print speed (colour, normal quality, A4/US Letter)	17 ppm	<b>Network</b>	
Warm-up time	90 s	Wi-Fi *	✓
Time to first page (black, normal)	5.8 s	Ethernet LAN *	✓
N-in-1 print function	✓	Cabling technology	10/100Base-T(X)
Watermark printing	✓	Ethernet LAN data rates	10,100 Mbit/s
Secure printing	✓	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Booklet printing function	✓	Security algorithms	EAP-MD5, EAP-TLS, EAP-TTLS, LEAP, PEAP, WEP, WMM, WPA, WPA-TKIP, WPA2, WPA2-Enterprise
<b>Copying</b>		Embedded web server	✓
Duplex copying *	✓	IP address filtering	✓
Copying *	Mono copying	Mobile printing technologies	Apple AirPrint, Mopria Print Service
Maximum copy resolution *	600 x 600 DPI	<b>Performance</b>	
Maximum copy size	A4	Internal memory *	512 MB
Duplex copy speed (black, US Letter)	17 ppm	Built-in processor	✓
Time to first copy (black, normal)	5.3 s	Processor frequency	1000 MHz
Maximum number of copies	9999 copies	Processor cores	2
Copier resize	-25 - 400%	Sound pressure level (printing)	67.1 dB

<b>Copying</b>		<b>Performance</b>	
N-in-1 copy function	✓	Sound power level (standby)	3.1 dB
N-in-1 copy function (N=)	2, 4	<b>Design</b>	
<b>Scanning</b>		Product colour *	Blue, White
Duplex scanning *	✓	Market positioning *	Home & office
Scanning *	Colour scanning	Built-in display *	✓
Optical scanning resolution *	600 x 600 DPI	Display	LCD
Optical scanning resolution (black)	600 x 600 ppi	Display diagonal	7.11 cm (2.8")
Optical scanning resolution (colour)	600 x 600 ppi	Control type	Touch
Maximum scan area	105 x 148 mm	Colour display	✓
Scanner type *	Flatbed & ADF scanner	<b>Power</b>	
Scan technology	CIS	Power consumption (max)	530 W
Scan to	E-mail, FTP, File, Network folder, USB	Power consumption (printing)	315 W
Image formats supported	BMP, GIF, JPG, PCX, PNG, TIFF	Power consumption (standby)	6.5 W
Document formats supported	PDF	Power consumption (sleep)	0.8 W
Input colour depth	24 bit	Power consumption (off)	0.1 W
Output colour depth	24 bit	AC input voltage	220 - 240 V
Scan drivers	ICA, TWAIN, WIA	AC input frequency	47-63 Hz
<b>Fax</b>		<b>System requirements</b>	
Faxing *	✗	Windows operating systems supported	Windows 10, Windows 11, Windows 8, Windows 8.1
<b>Features</b>		Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur
Recommended duty cycle	0 - 6000 pages per month	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2019
Maximum duty cycle *	80000 pages per month	<b>Operational conditions</b>	
Duplex functions *	Copy, Print	Operating relative humidity (H-H)	8 - 80%
Number of print cartridges *	1	Storage temperature (T-T)	-40 - 40 °C
Printing colours *	Black	Operating temperature (T-T)	10 - 32.2 °C
Page description languages	PCL 5, PCL 6, PostScript 3	Storage relative humidity (H-H)	8 - 80%
Printer fonts	Bitmap, PCL, PostScript, Scalable	<b>Sustainability</b>	
Number of PCL fonts	6	Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT
Number of PostScript fonts	158	<b>Weight &amp; dimensions</b>	
Number of bitmap fonts	2	Width	411 mm
Number of scalable fonts	89	Depth	266 mm
<b>Input &amp; output capacity</b>		Height	339 mm
Total number of input trays *	2	Weight	12.8 kg
Total input capacity *	350 sheets	<b>Packaging data</b>	
Total output capacity *	100 sheets	Package width	420 mm
Paper tray 1 input capacity	250 sheets	Package depth	470 mm
Multi-Purpose tray	✓	Package height	390 mm
Multi-Purpose tray input capacity	100 sheets	Package weight	14.7 kg
Auto document feeder (ADF)	✓	<b>Packaging content</b>	
Auto document feeder (ADF) input capacity	50 sheets	Cartridge(s) included	✓
<b>Paper handling</b>		Included cartridge capacity (black)	2500 pages
Maximum ISO A-series paper size *	A4	Cables included	AC
Paper tray media types *	Bond paper, Card stock, Envelopes, Glossy paper, Heavy paper, Labels, Letterhead, Plain paper, Pre-printed, Recycled paper, Rough paper	Drivers included	✓
		Power cord included	✓
ISO A-series sizes (A0...A9) *	A4, A5, A6	Quick installation guide	✓
ISO B-series sizes (B0...B9)	B5	<b>Logistics data</b>	
ISO C-series sizes (C0...C9)	C5	Harmonized System (HS) code	84433100
Non-ISO print media sizes	Folio, Legal, Oficio, Statement	<b>Other features</b>	
JIS B-series sizes (B0...B9)	B5	Web-based management	✓
Envelopes sizes	C5	Maximum scan area (ADF)	216 x 356 mm
Custom media width	99 - 216 mm		

## Other features

Supported network protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD- Print 802.1x, SNMP
Software CD	✓
Documentation CD	✓



0095205069372



095205069372



0095205069389



095205069389

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.