

Xerox B315, A4, 40 s/min, langaton, kaksipuolinen kopiointi/tulostus/skannaus/faksaus, PS3 PCL5e/6 , 2 alustaa, 350 arkkia

Tuotemerkki : Xerox

Tuotekoodi: B315V_DNI

Tuotteen nimi : Xerox B315, A4, 40 s/min, langaton, kaksipuolinen kopiointi/tulostus/skannaus/faksaus, PS3 PCL5e/6 , 2 alustaa, 350 arkkia

- Kopiointi, tulostus, skannaus, faksi
- Sopii erinomaisesti pk-yrityksille ja kotitoimistoihin
- Pääsy valinnaiseen edistyneeseen asiakirjojen työnkulkuun Xerox Workflow Centralin avulla
- Luotettava ja varma
- Valmis mobiilikäyttöön: Apple AirPrint, Mopria, Wi-Fi Direct
- Kattavat suojaustoiminnot

Xerox B315, A4, 40 s/min, langaton, kaksipuolinen kopiointi/tulostus/skannaus/faksaus, PS3 PCL5e/6 , 2 alustaa, 350 arkkia



Printing		Paper handling	
Duplex printing mode	Auto	Non-ISO print media sizes	Folio, Legal, Oficio, Statement
Print resolution black	600 x 600 DPI	JIS B-series sizes (B0...B9)	B5
Print technology *	Laser	Envelopes sizes	C5
Printing *	Mono printing	Custom media width	99 - 216 mm
Duplex printing *	✓	Custom media length	148 - 360 mm
Maximum resolution *	2400 x 2400 DPI	Paper tray media weight	60 - 120 g/m ²
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Multi-Purpose Tray media weight	60 - 217 g/m ²
Print speed (colour, normal quality, A4/US Letter)	40 ppm	Auto Document Feeder (ADF) media weight	60 - 90 g/m ²
Duplex print speed (black, normal quality, A4/US Letter)	18 ppm	Duplex media weight	60 - 90 g/m ²
Duplex print speed (colour, normal quality, A4/US Letter)	18 ppm		
Warm-up time	90 s	Ports & interfaces	
Time to first page (black, normal)	5.8 s	Direct printing *	✓
N-in-1 print function	✓	USB port	✓
Watermark printing	✓	USB connector	USB Type-A / USB Type-B
Secure printing	✓	Network	
Booklet printing function	✓	Wi-Fi *	✓
		Ethernet LAN *	✓
		Cabling technology	10/100Base-T(X)
		Ethernet LAN data rates	10,100 Mbit/s
		Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
		Security algorithms	EAP-MD5, EAP-TLS, EAP-TTLS, LEAP, PEAP, WEP, WMM, WPA, WPA-TKIP, WPA2, WPA2-Enterprise
		Embedded web server	✓
		IP address filtering	✓
		Mobile printing technologies	Apple AirPrint, Mopria Print Service
		Performance	
		Internal memory *	512 MB
Copying			
Duplex copying *	✓		
Copying *	Mono copying		
Maximum copy resolution *	600 x 600 DPI		
Maximum copy size	A4		
Duplex copy speed (black, US Letter)	17 ppm		
Time to first copy (black, normal)	5.3 s		
Maximum number of copies	9999 copies		
Copier resize	-25 - 400%		

Copying		Performance	
N-in-1 copy function	✓	Built-in processor	✓
N-in-1 copy function (N=)	2, 4	Processor frequency	1000 MHz
Scanning		Processor cores	2
Duplex scanning *	✓	Sound pressure level (printing)	67.1 dB
Scanning *	Colour scanning	Sound power level (printing)	67.1 dB
Optical scanning resolution *	600 x 600 DPI	Sound power level (standby)	3.1 dB
Optical scanning resolution (black)	600 x 600 ppi	Design	
Optical scanning resolution (colour)	600 x 600 ppi	Product colour *	Blue, White
Maximum scan area	216 x 297 mm	Market positioning *	Home & office
Scanner type *	Flatbed & ADF scanner	Built-in display *	✓
Scan technology	CIS	Display	LCD
Scan to	E-mail, FTP, File, Network folder, USB	Display diagonal	7.11 cm (2.8")
Image formats supported	GIF, TIFF, JPG	Control type	Touch
Document formats supported	PDF	Colour display	✓
Input colour depth	24 bit	Power	
Output colour depth	24 bit	Power consumption (max)	580 W
Scan drivers	ICA, TWAIN, WIA	Power consumption (printing)	360 W
Fax		Power consumption (standby)	7.5 W
Duplex faxing	✓	Power consumption (sleep)	1.1 W
Faxing *	Colour faxing	Power consumption (off)	0.1 W
Fax resolution (black)	600 x 600 DPI	AC input voltage	220 - 240 V
Fax resolution (colour)	600 x 600 DPI	AC input frequency	47-63 Hz
Modem speed	33.6 Kbit/s	System requirements	
Fax memory	6 MB	Windows operating systems supported	Windows 10, Windows 11, Windows 8, Windows 8.1
Auto-redialing	✓	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur
Fax forwarding to	E-mail, FTP, Fax	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2019
Fax delayed sending	✓	Operational conditions	
Auto reduction	✓	Operating relative humidity (H-H)	8 - 80%
Fax coding methods	JBIG, JPEG, MH, MMR, MR	Storage temperature (T-T)	-40 - 40 °C
Features		Operating temperature (T-T)	10 - 32.2 °C
Recommended duty cycle	0 - 6000 pages per month	Storage relative humidity (H-H)	8 - 80%
Maximum duty cycle *	80000 pages per month	Sustainability	
Duplex functions *	Copy, Print, Scan	Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT
Number of print cartridges *	1	Weight & dimensions	
Printing colours *	Black	Width	411 mm
Page description languages	PCL 5, PCL 6, PostScript 3	Depth	266 mm
Printer fonts	Bitmap, PCL, PostScript, Scalable	Height	339 mm
Number of PCL fonts	6	Weight	12.8 kg
Number of PostScript fonts	158	Packaging data	
Number of bitmap fonts	2	Package width	420 mm
Number of scalable fonts	89	Package depth	470 mm
Input & output capacity		Package height	390 mm
Total number of input trays *	2	Package weight	14.7 kg
Total input capacity *	350 sheets	Packaging content	
Total output capacity *	100 sheets	Cartridge(s) included	✓
Paper tray 1 input capacity	250 sheets	Included cartridge capacity (black)	2500 pages
Multi-Purpose tray	✓	Cables included	AC
Multi-Purpose tray input capacity	100 sheets	Drivers included	✓
Auto document feeder (ADF)	✓	Power cord included	✓
Auto document feeder (ADF) input capacity	50 sheets	Quick installation guide	✓
Paper handling			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Bond paper, Card stock, Envelopes, Glossy paper, Heavy paper, Labels, Letterhead, Plain paper, Pre-printed, Recycled paper, Rough paper		

Paper handling		Logistics data	
ISO A-series sizes (A0...A9) *	A4, A5, A6	Export Control Classification Number (ECCN)	EAR99
ISO B-series sizes (B0...B9)	B5	Harmonized System (HS) code	84433100
ISO C-series sizes (C0...C9)	C5	Other features	
		Web-based management	✓
		Maximum scan area (ADF)	216 x 356 mm
		Supported network protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print 802.1x, SNMP
		Software CD	✓
		Documentation CD	✓



0095205069396



095205069396



0095205069419



095205069419

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.