ASUS PRIME H510M-K R2.0 Intel H510 LGA 1200 (Socket H5) mikro ATX

Tuotemerkki : ASUS Tuotekoodi: 90MB1E80-M0EAY0

Tuotteen nimi: PRIME H510M-K R2.0

ASUS PRIME H510M-K R2.0. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1200 (Socket H5), Yhteensopivat prosessorit: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 64 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, Tuetut tallennusasematyypit: HDD & SSD. Ethernetliitännän tyyppi: Nopea Ethernet, Gigabitti Ethernet. Komponentti (tuotteelle): PC, Emolevyn muototekijä: mikro ATX, Emolevyn piirisarjan perhe: Intel







Processor		Internal I/O	
Processor manufacturer * Processor socket *	Intel LGA 1200 (Socket H5) Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7,	EPS power connector (8-pin) TPM connector 12V power connector	
Compatible processor series *	Intel® Core™ i9, Intel® Pentium® Gold	Rear panel I/O ports	
Memory	DDD4 CDD4M	USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	2
Supported memory types * Number of memory slots *	DDR4-SDRAM 2 DIMM	ports quantity * Ethernet LAN (RJ-45) ports *	1
Memory slots type Memory channels ECC compatibility	Dual-channel Non-ECC	PS/2 ports quantity VGA (D-Sub) ports quantity *	1
Supported memory clock speeds	2133,2400,2666,2800,2933,3000,3200 MHz	COM ports quantity	1
Maximum internal memory *	64 GB	Network	
Unbuffered memory	✓	Ethernet LAN	✓
Storage controllers		Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Supported storage drive types	HDD & SSD	Wi-Fi *	×
Supported storage drive interfaces	* M.2, SATA III	Features	
Number of HDDs supported Number of storage drives supported	4 d 5	Motherboard chipset * Audio output channels *	Intel H510 7.1 channels
Internal I/O		Component for *	PC
USB 2.0 connectors *	2	Motherboard form factor *	micro ATX
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Motherboard chipset family * Windows operating systems	Intel Windows 10 x64
Number of SATA III connectors *	4	supported	
S/PDIF out connector	✓	Expansion slots	
Front panel audio connector	✓	PCI Express x1 (Gen 3.x) slots	1
ATX Power connector (24-pin)	1	Number of M.2 (M) slots	1

Internal I/O		BIOS	
CPU fan connector Number of chassis fan connectors	1	BIOS type * BIOS memory size	EFI AMI 128 Mbit
		Mainbt Calinanaiana	
		Weight & dimensions	
		Width	226 mm



4711387113189

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.