
## QNAP

## QNAP TS-1264U-RP NAS Teline ( 2U ) Intel® Celeron® 8 GB DDR4 0 TB QNAP QTS Alumiini, musta

Tuotemerkki : QNAP Tuotekoodi: TS-1264U-RP-8G

Tuotteen nimi: TS-1264U-RP







Storage		Performance	
Supported storage drive interfaces Storage drive sizes supported	Serial ATA II, Serial ATA III 2.5,3.5"	Type * Device class *	NAS Small & Medium Business
RAID support *	<b>✓</b>	Backup function *	<b>✓</b>
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Backup features	Cloud, iSCSI LUN
Online RAID migration	✓	Buzzer	✓
Online RAID expansion	✓	Multilingual support	✓
RAID rebuild	✓	Snapshot	✓
Hot-swap drive bays	✓	Management protocols	SNMP
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3,	Web-based management	✓
Storage drives installed *	ext4	Share folder access right management	✓
Total installed storage capacity *	0 TB	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMP
Number of storage drives supported *	12	Access Control List (ACL)	✓
Installed storage drive type *	×	Reset button	✓
Supported storage drive types *	HDD & SSD	On/off switch	✓
Bad block scan	✓	Built-in FTP server	✓
Disk roaming	<b>✓</b>	Browser supported	Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox
Processor		System log	<b>✓</b>
Processor manufacturer *	Intel	Hot spare	<b>✓</b>
Processor family *  Processor frequency *	Intel® Celeron® 2 GHz	Disk scan	<b>✓</b>
Processor boost frequency	2.9 GHz	S.M.A.R.T. support	✓
Processor cores	4	Share folder	CIFS/SMB
Processor threads	4	Universal Plug and Play (UPnP)	✓
On-board graphics card model	Intel® UHD Graphics	USB copy function	✓
Memory		Software	
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory	8 GB DDR4 16 GB 2 SO-DIMM 4000 MB	Operating system installed * Operating system version	QNAP QTS 5.0.0

Network		Software	
Ethernet LAN * Ethernet LAN data rates DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system Dynamic DNS (DDNS) WLAN adapter supported	PPTP, L2TP/IPSec, OpenVPN, QBelt	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise,
USB port * USB 2.0 ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	<ul><li>2</li><li>2</li><li>2</li></ul>	Linux operating systems supported	Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 Ubuntu 14.04 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
HDMI ports quantity HDMI version Ethernet LAN (RJ-45) ports *  Design	1 1.4b 2	Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina
Chassis type * Cooling type * Product colour	Rack (2U) Active Aluminium, Black	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Number of fans	2 fan(s)	Other operating systems supported	Solaris 10
Fan diameter	8 cm	Power	
Fan diameter 2 LED indicators	8 cm LAN, Power, Status	Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage	Built-in 300 W 2 ✓ 70.913 W 37.854 W 100 - 240 V
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical)	300 W 2 • 70.913 W
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage	300 W 2 ✓ 70.913 W 37.854 W 100 - 240 V
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency	300 W 2 ✓ 70.913 W 37.854 W 100 - 240 V 50 - 60 Hz
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency Fan voltage	300 W 2 ✓ 70.913 W 37.854 W 100 - 240 V 50 - 60 Hz
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency Fan voltage  Weight & dimensions  Width * Depth * Height * Weight	300 W 2  70.913 W 37.854 W 100 - 240 V 50 - 60 Hz 12 V  482.2 mm 423.8 mm 88.7 mm 9.43 kg
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency Fan voltage  Weight & dimensions  Width * Depth * Height * Weight Package weight	300 W 2  70.913 W 37.854 W 100 - 240 V 50 - 60 Hz 12 V  482.2 mm 423.8 mm 88.7 mm 9.43 kg
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency Fan voltage  Weight & dimensions  Width * Depth * Height * Weight Package weight  Packaging content Cables included	300 W 2  70.913 W 37.854 W 100 - 240 V 50 - 60 Hz 12 V  482.2 mm 423.8 mm 88.7 mm 9.43 kg 14.1 kg  AC, LAN (RJ-45)
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency Fan voltage  Weight & dimensions  Width * Depth * Height * Weight Package weight  Packaging content Cables included Number of screws	300 W 2  70.913 W 37.854 W 100 - 240 V 50 - 60 Hz 12 V  482.2 mm 423.8 mm 88.7 mm 9.43 kg 14.1 kg  AC, LAN (RJ-45)
	8 cm	Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Power consumption (sleep) AC input voltage AC input frequency Fan voltage  Weight & dimensions  Width * Depth * Height * Weight Package weight  Packaging content  Cables included Number of screws  Operational conditions  Operating relative humidity (H-H)	300 W 2  70.913 W 37.854 W 100 - 240 V 50 - 60 Hz 12 V  482.2 mm 423.8 mm 88.7 mm 9.43 kg 14.1 kg  AC, LAN (RJ-45) 48  0 - 40 °C 5 - 95%





4711103082416

7330381219290

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.