



Introduction

The Atlona **AT-OME-EX-TX-WPC** is an HDBaseT transmitter with USB-C input. It sends video up to 4K/30 4:4:4, plus embedded audio, control, and USB over distances up to 330 feet (100 meters). It features a US one-gang, Decora-style wallplate form factor, and includes interchangeable black and white wallplates and faceplates. Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-EX-TX-WPC is HDCP 2.2 compliant and extends RS-232 control signals. The USB-C input is ideal for AV interfacing with newer Mac®, Chromebook™, and Windows® PCs, as well as smartphones and tablets. With a matching HDBaseT receiver, the integrated USB extension addresses the challenge of connecting between USB devices at remote locations, and is ideal for software video conferencing and touch or interactive displays. The OME-EX-TX-WPC includes a PC host interface over USB-C, plus a USB 2.0 interface for a peripheral device such as a speakerphone, microphone, or keyboard and mouse. This transmitter is ideal for use with Omega Series receivers as well as switchers with HDBaseT inputs.⁽¹⁾

Applications

- **Complete system integration**
The OME-EX-TX-WPC and OME-SR21 together provide a compact, yet comprehensive and cost-effective integration solution, with 4K scaling, display control, HDBaseT link testing, and audio system interfacing provided by the receiver.
- **Lecture hall and training room applications**
This transmitter is ideal for extending AV connectivity from an OME-PS62 in a central equipment rack to lecterns as well as remote wall and floor box locations, where presenters can easily access the system.
- **Video conferencing**
The OME-EX-TX-WPC and a compatible Omega Series receiver or switcher are ideal for soft codec and web-based conferencing applications, with the ability to integrate with PCs, cameras, speakerphones, and microphones.

Key Features

US one-gang enclosure for Decora-style wallplate openings – interchangeable black or white trim kits

- Allows inconspicuous installation on a wall, in furniture, or in a floor box. Includes black and white wallplates and faceplates.
- Meets end user requirements for conveniently accessible yet discreet AV connectivity.

USB-C input for AV and data

- Immediate compatibility with laptops and tablets with USB-C ports supporting AV⁽²⁾.
- No need to provide USB-C to HDMI adapters.

Video, audio, power, and data over category cable utilizing HDBaseT technology

- Transmits 4K/UHD video up to 330 feet (100 meters) with CAT6/6a/7 cable, or up to 295 feet (90 meters) using CAT5e cable.
- Uses easy-to-integrate category cable for low-cost, reliable system installation.

USB 2.0 interfacing and extension up to 330 feet (100 meters)

- USB-C interface for connection to a host PC, plus a USB type A port for a peripheral device such as a microphone, speakerphone, or a keyboard and mouse.
- Provides an ideal USB integration solution for software video conferencing, and applications with interactive collaboration⁽³⁾.

4K/UHD capability @ 30 Hz with 4:4:4 chroma subsampling

- Transmits high resolution video up to and including 4K/UHD @ 30Hz 4:4:4 8 bit.
- Supports video data rates up to 10 Gbps from PCs, media players, and Ultra HD Blu-ray players.

HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

Remote powering over HDBaseT

- Industry standard IEEE 802.3af PoE is supplied by an Atlona receiver or switcher over HDBaseT.
- Allows convenient wall, floor box, or furniture installation without the need for local AC power.

Specifications

Video	
Signal Type	Input - DisplayPort Alternate Mode (USB-C) Output - HDBaseT
Copy Protection	HDCP 1.4/2.2
Pixel Clock	300MHz
UHD/HD/SD	4096x2160(DCI)@30/24 Hz 3840x2160(UHD)@30/25/24 Hz 2560x1440@30 Hz 1920x1080p@60/59.94/50/30/29.97/25 /24/23.98 Hz 1920x1080i@30/29.97/25 Hz 1280x720p@60/59.94/50/30 Hz 720x576i/p@50 Hz 720x480i/p@60 Hz
VESA All resolutions are 60Hz	2560x1600 1920x1200 1680x1050 1600x1200 1440x900 1400x1050 1280x1024 1280x800 1366x768 1360x768 1152x864 1024x768 800x600 640x480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4
Color Depth	8-bit, 10-bit, 12-bit

Audio			
Pass-Through	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Rate	24 Mbits/s max		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

USB	
Signal	2.0
Maximum Data Rate	120 Mbps

RS-232	
Default Parameters	115200, 8-bit, None, 1
Use	Connected display or source control
Baud Rates	2400, 4800, 9600, 19200, 38400, 57600, 115200
Data flow	Bidirectional

Connectors	
USB-C	1 - USB Type-C v3.1, 24-pin female
HDBaseT OUT	1 - RJ45
DEVICE	1 - USB Type-A
RS-232	1 - captive screw, 3-pin

Indicators and Controls				
PWR LED indicator	1 - LED, green			
LINK LED indicator	1 - LED, yellow			

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
USB-C	6	2	6	2
CAT5e	295	90	330	100
CAT6/6a/7	330	100	330	100

Power	
Consumption	Unit only: 8.68 W Full load: 11.18 W (while powering a USB type A device up to 2.5 W)
Supply	PoE via connected receiver
BTU/h	Unit only: 29.6 Full load: 34.1 (while powering a USB type A device up to 2.5 W)

Temperature	Fahrenheit	Celsius
Operating	+32 to +104	0 to +40
Storage	-4 to 140	-20 to 60
Humidity (RH)	20% to 60%, non-condensing	

Dimensions (H x W x D)	Inches	Millimeters
Unit	4.07 x 1.80 x 2.63	103.50 x 45.80 x 67.00

Weight	Pounds	Kilograms
Device	0.40	0.18

Certification	
Device	CE, RoHS, FCC

Compliance	
NDAA-899	Yes

Footnotes

- 1 The OME-EX-TX-WPC is not compatible with the Atlona HDVS-300 system for USB extension.
- 2 USB-C port does not support device powering.
- 3 Maximum 120 Mbps data rate supported over HDBaseT.

Copyright, Trademark, and Registration

© 2022 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).