



TP-Link Omada EAP613 WLAN-tukiasema 1775 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : TP-Link

Tuoteperhe: Omada

Tuotekoodi: EAP613

Tuotteen nimi : EAP613

TP-Link Omada EAP613. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1775 Mbit/s. Tietoturva-algoritmit: HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3. Ethernet LAN -datanopeudet: 100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen. Tehonkulutus (maks.): 10,6 W



Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Power over Ethernet (PoE) type supported	Passive PoE
6 GHz *	✗	DC voltage range	12 V
Maximum data transfer rate *	1775 Mbit/s	Input current	1 A
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Power consumption (typical)	9.6 W
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Power consumption (max)	10.6 W
Ethernet LAN data rates	100,1000 Mbit/s	Design	
Frequency band	2.4 - 5 GHz	Placement *	Ceiling, Wall
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Product colour *	White
Automatic channel selection	✓	Reset button	✓
Automatic channel scanning	✓	LED indicators	✓
MIMO	✓	Antenna	
MIMO type	Multi User MIMO	Antenna type *	Internal
Spread spectrum method	OFDMA	Antennas quantity	4
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna gain level (max)	5 dBi
VLAN support	✓	Performance	
Rate limiting	✓	Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Wireless isolation	✓	Certificates	
Band steering	✓	Certification	CE, FCC, RoHS
Airtime Fairness (ATF)	✓	Weight & dimensions	
BeamForming	✓	Width	160 mm

Features		Weight & dimensions	
Transmitting power (CE)	<20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz band1/2, EIRP); <25 dBm (5 GHz band3)	Depth	160 mm
Transmitting power (FCC)	<25 dBm (2.4 GHz); <25 dBm (5 GHz)	Height	33.6 mm
Security		Packaging content	
Security algorithms *	HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3	Quantity per pack	1 pc(s)
Number of SSID supported	16	Mounting kit	✓
Management features		Operational conditions	
Web-based management	✓	Operating relative humidity (H-H)	0 - 40%
Management platform	Omada	Operating temperature (T-T)	10 - 90 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN (RJ-45) ports *	1	Storage relative humidity (H-H)	5 - 90%
DC-in jack	✓		



4895252500516



0840030704307



840030704307

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.