

## Epson EU-M30 (002) 203 x 203 DPI Wired & Wireless Thermal POS printer

**Brand :** Epson

**Product code:** C31CK01002

**Product name :** EU-M30 (002)



- Compact and efficient with easy mounting kit
- Remote monitoring support for less downtime
- New bezel option for fewer paper jams
- Bright LED alerts for quick troubleshooting
- Security features prevent unauthorized access
- Available in black and white

EU-m30 Kiosk Thermal Receipt Printer

Epson EU-M30 (002). Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite). Connectivity technology: Wired & Wireless. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: Black



<b>Printing</b>		<b>Operational conditions</b>	
Maximum resolution	203 x 203 DPI	Operating temperature (T-T)	5 - 45 °C
Print speed (receipt)	250 mm/sec	Operating relative humidity (H-H)	10 - 90%
Printing characters	Text, Graphic, Barcode	Storage relative humidity (H-H)	10 - 90%
Character sets	ANK	<b>System requirements</b>	
Print technology *	Thermal	Pre-installed software	TMNet WebConfig, ePOS-Device, ePOS-Display, ePOS-Print
Type *	POS printer	<b>Weight &amp; dimensions</b>	
<b>Paper handling</b>		Width	127 mm
Maximum roll diameter	8.3 cm	Depth	131 mm
Supported paper width	58 mm - 80 mm (Breite)	Height	127 mm
<b>Ports &amp; interfaces</b>		Weight	1.3 kg
USB port *	✓	<b>Packaging data</b>	
Serial interface *	✓	Quantity per pack	1 pc(s)
Connectivity technology *	Wired & Wireless	Package width	195 mm
Near Field Communication (NFC)	✓	Package depth	230 mm
<b>Features</b>		Package height	235 mm
Sound pressure level (printing)	55 dB	Package weight	1.65 kg
Mean time between failures (MTBF)	360000 h	<b>Print technology</b>	
Half-cutter	✓	Column capacity	48/57
Autocutter durability	1.5 million cuts	<b>Logistics data</b>	
Print head life	150 km	Harmonized System (HS) code	84433210
Country of origin	Philippines	<b>Technical details</b>	
Mounting position	Horizontal	Font styles	ANK
Built-in sensors details	Paper End Sensor, Papier-Sensor	Lifetime	17000000 lines
<b>Design</b>		<b>Other features</b>	
Product colour *	Black	Buffer size	12 KB
<b>Power</b>		Mean cycles between failures (MCBF)	65000000
Power plug type	Type C	Print head life	150.000.000 Impulse



8715946700137

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-NOV-2024. Prints or copies of Information are only valid on the printed Publication date