



## APC SRTL1500RM4UXLI-NC UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1,5 kVA 1350 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRTL1500RM4UXLI-NC

Tuotteen nimi : SRTL1500RM4UXLI-NC



APC SRTL1500RM4UXLI-NC. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 1350 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun kapasiteetti: 2400 ah, Akun jännite: 48 V. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Hopea, Telineen kapasiteetti: 4U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 590 mm, Tuotteen korkeus: 171 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	177 min
Output power capacity *	1.5 kVA	Battery life (max)	10 year(s)
Output power *	1350 W	<b>Design</b>	
Waveform *	Sine	Form factor *	Rackmount/Tower
Input operation voltage (min) *	160 V	Rack capacity	4U
Input operation voltage (max) *	275 V	Cable length	1.83 m
Input frequency *	40/70 Hz	Modular	✓
Output operation voltage (min)	220 V	Product colour *	Black, Silver
Output operation voltage (max)	230 V	Control type	Buttons
Output frequency	50/60 Hz	Display type	LCD
Surge energy rating	340 J	International Protection (IP) code	IP20
Crest factor	3:1	Certification	RoHS, CE
Emergency Power Off (EPO)	✓	<b>Operational conditions</b>	
Noise level	50 dB	Operating temperature (T-T)	0 - 40 °C
Audible alarm(s)	✓	Storage temperature (T-T)	-15 - 45 °C
Power source type	AC	Operating relative humidity (H-H)	0 - 95%
Detachable power cord	✓	Storage relative humidity (H-H)	0 - 95%
<b>Ports &amp; interfaces</b>		Operating altitude	0 - 3048 m
AC outlet types	C13 coupler	Non-operating altitude	0 - 15240 m
Power plug	C14 coupler	<b>Technical details</b>	
AC outlets quantity	8 AC outlet(s)	Sustainability certificates	Green Premium
USB 2.0 ports quantity	2	Compliance certificates	CE, RoHS
Ethernet LAN (RJ-45) ports	1	<b>Weight &amp; dimensions</b>	
<b>Battery</b>		Width	432 mm
Battery technology	Lithium-Ion (Li-Ion)	Depth	590 mm
Battery capacity	2400 Ah	Height	171 mm
Battery voltage	48 V	Weight	40.7 kg
Typical backup time at full load	93 min		

**Packaging data**

Rack mount kit





0731304508960



731304508960



8592978475307

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.