

# Product data sheet

Specifications



APC Smart-UPS On-Line, 3kVA,  
Lithium-ion, Rackmount 4U, 230V,  
6x C13+2x C19 IEC outlets, Network  
Card, Extended long runtime, Rail kit  
included

SRTL3000RM4UXLI-NC

## Overview

Presentation	High density, double-conversion on-line power protection with long runtime with NMC
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Input Connection Type	IEC 60320 C20
Nb of power socket outlets	6 IEC 60320 C13
Number of rack unit	4U
Cable length	6 ft (1.83 m)
Number of cables	1
Battery Type	Li-Ion (Lithium Ion)

## General

Product web sub-family	Lithium Ion
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Color	Black with silver front bezel
Height	6.73 in (17.1 cm)
Width	17.01 in (43.2 cm)
Depth	25.16 in (63.9 cm)

<b>Net Weight</b>	98.11 lb(US) (44.5 kg)
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Rack-mounted with kit
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Horizontal Vertical

## Input

<b>Input Frequency</b>	40 - 70 Hz auto-sensing
<b>Efficiency at full load</b>	160...275 V

## Output

<b>Max Configurable Power (Watts)</b>	2700 W
<b>Harmonic distortion</b>	Less than 2%
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
<b>Crest factor</b>	3 : 1
<b>Topology</b>	Double Conversion Online
<b>Waveform Type</b>	Sine wave
<b>Bypass type</b>	Built-in Bypass
<b>Maximum configurable power in VA</b>	3000 VA

## Conformance

<b>Product Certifications</b>	CE
<b>Marking</b>	CE Mark

## Environmental

<b>Ambient air temperature for operation</b>	32...104 °F (0...40 °C)
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-4...122 °F (-20...50 °C)
<b>Storage Relative Humidity</b>	0...95 % Non-condensing
<b>Storage altitude</b>	0...50000 ft (0.00...15240.00 m)
<b>Acoustic level</b>	50 dBA
<b>Heat dissipation</b>	317 Btu/h
<b>IP degree of protection</b>	IP20

## Batteries & Runtime

<b>Included Battery Modules</b>	0
<b>Battery Slots Empty</b>	0
<b>Battery voltage</b>	48V
<b>Battery Charge Power (Watts)</b>	158 W rated
<b>Battery power in VAH</b>	2400 VAh capacity 2880 VAh runtime

---

<b>Battery life</b>	5...10 year(s)
<b>Battery option</b>	XBP48RM2U-LI 1 5760 VAh XBP48RM2U-LI 2 8640 VAh
<b>Extendable Run Time</b>	1

---

## Communications & Management

---

<b>Free slots</b>	0
<b>Pre-Installed SmartSlot™ Cards</b>	Network management card 2 with environmental monitoring
<b>Audible Alarm</b>	Audible and visible alarms prioritized by severity
<b>Emergency Power Off (EPO)</b>	Yes

---

## Surge Protection and Filtering

---

<b>Surge energy rating</b>	432 J
----------------------------	-------

---

## Ordering and shipping details

---

<b>GTIN</b>	731304509004
-------------	--------------

---

## Contractual warranty

---

<b>Warranty</b>	5 year repair or replace
-----------------	--------------------------

---