# StarTech.com DKT31CVHPD3 kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 2 (3.1 Gen 2) Type-C Harmaa

Tuotemerkki : StarTech.com

Tuotekoodi: DKT31CVHPD3

Tuotteen nimi : DKT31CVHPD3

StarTech.com DKT31CVHPD3. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, USB Power Delivery asti: 100 W. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Tuotteen väri: Harmaa, Tiedonsiirtonopeus: 10 Gbit/s, HD-tyyppi: 4K Ultra HD. Virrankulutus: 16 W, USB-kaapelin pituus: 0,32 m. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac-käyttöjärjestelmätuki: Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey,..., Linux-käyttöjärjestelmätuki: Ubuntu 18.04 LTS, Ubuntu 20.04 LTS

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	100 W
HDMI ports quantity *	1
HDMI version	2.0b
VGA (D-Sub) ports quantity	1
Microphone in *	✘

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Full duplex	✔

Performance

Card reader integrated *	✘
Data transfer rate	10 Gbit/s
HD type	4K Ultra HD
Maximum digital resolution	4096 x 2160 pixels
Maximum analog resolution	1920 x 1200 pixels
Maximum refresh rate	60 Hz
Product colour *	Grey
LED indicators	✔

Software

Mac operating systems supported	Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Linux operating systems supported	Ubuntu 18.04 LTS, Ubuntu 20.04 LTS
Mobile operating systems supported	Android
Other operating systems supported	ChromeOS

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 55 °C
Operating relative humidity (H-H)	0 - 85%

Sustainability

Sustainability compliance	✔

Weight & dimensions

Width	64 mm
Depth	124 mm
Height	25 mm
Weight	130 g

Packaging data

Package width	142 mm
Package depth	170 mm
Package height	30 mm
Package weight	154 g

Packaging content

Quick start guide	✔

Performance

UASP support	✔
Housing material	Plastic

Power

Power consumption (typical)	16 W
USB cable length	0.32 m

Software

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64

Technical details

Compliance certificates	CE, RoHS

Logistics data

Products per master (outer) case	70 pc(s)
Master (outer) case width	473 mm
Master (outer) case length	331 mm
Master (outer) case height	440 mm

Other features

Chipset	Realtek - RTD2142, Realtek - RTL8153B, VIA - VL822-Q8, VIA - VL103

0065030891998

065030891998