



DELL P Series P1917S computer monitor 48.3 cm (19") 1280 x 1024 pixels SXGA LCD Black

Brand : DELL

Product family: P Series

Product code: DELL-P1917SE

Product name : P1917S

- 48.26 cm (19") SXGA LED IPS 1280 x 1024
- 6 ms, 5:4, 250cd/m², 1000:1
- 1 VGA, 1 HDMI, 1 DisplayPort
- 19" LED IPS (1280 x 1024), 5:4, 250cd/m², 16.78M, 6ms, 178°/178°, 1000:1

DELL P Series P1917S computer monitor 48.3 cm (19") 1280 x 1024 pixels SXGA LCD Black:

Dell 19 Monitor | P1917S brings greater productivity to the workplace with added user comfort and convenience.

DELL P Series P1917S. Display diagonal: 48.3 cm (19"), Display resolution: 1280 x 1024 pixels, HD type: SXGA, Display technology: LCD. Display: LED. Response time: 6 ms, Native aspect ratio: 5:4, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Power	
Display diagonal *	48.3 cm (19")	Energy efficiency class (SDR) *	D
Display resolution *	1280 x 1024 pixels	Energy efficiency class (HDR) *	Not available
HD type *	SXGA	Energy consumption (SDR) per 1000 hours *	11 kWh
Native aspect ratio *	5:4	Power consumption (typical) *	14 W
Display technology *	LCD	Power consumption (standby) *	0.3 W
Panel type *	IPS	Power consumption (max)	38 W
Backlight type	LED	Power consumption (off)	0.3 W
Touchscreen *	✗	Power consumption (PowerSave)	13 W
Display brightness (typical)	250 cd/m ²	AC input voltage	100 - 240 V
Response time *	6 ms	AC input frequency	50 - 60 Hz
Screen shape *	Flat	Input current	1.5 A
Supported graphics resolutions	1280 x 1024 (SXGA)	Power supply type	Internal
Contrast ratio (typical) *	1000:1	European Product Registry for Energy Labelling (EPREL) code	344219
Contrast ratio (dynamic)	4000000:1	Annual energy consumption	17 kWh
Maximum refresh rate *	60 Hz	Operational conditions	
Viewing angle, horizontal	178°	Operating temperature (T-T)	0 - 40 °C
Viewing angle, vertical	178°	Storage temperature (T-T)	-20 - 60 °C
Display number of colours *	16.78 million colours	Operating relative humidity (H-H)	20 - 80%
Pixel pitch	0.293 x 0.293 mm	Storage relative humidity (H-H)	10 - 90%
Pixel density	86 ppi	Operating altitude	0 - 5000 m
Horizontal scan range	30 - 81 kHz	Non-operating altitude	5000 - 12192 m
Vertical scan range	56 - 76 Hz	Weight & dimensions	
Viewable size, horizontal	37.5 cm	Width (with stand)	405.6 mm
Viewable size, vertical	30 cm	Depth (with stand)	180 mm
Viewable size diagonal	48 cm	Height (with stand)	499.3 mm
High Dynamic Range (HDR) supported	✗	Weight (with stand)	5.13 kg
3D	✗	Width (without stand)	405.6 mm

Performance		Weight & dimensions	
NVIDIA G-SYNC *	✗	Depth (without stand)	50.3 mm
AMD FreeSync *	✗	Height (without stand)	334.3 mm
Multimedia		Weight (without stand)	2.6 kg
Built-in speaker(s) *	✗	Packaging content	
Built-in camera *	✗	Stand included	✓
Design		Cables included	AC, DisplayPort, USB, VGA
Market positioning *	Home	Sustainability	
Product colour *	Black	Sustainability certificates	ENERGY STAR
Ports & interfaces		Carbon footprint	
Built-in USB hub *	✓	Total carbon footprint (kg of CO2e)	433
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Total carbon emissions, standard deviation (kg of CO2e)	86
USB upstream port type	USB Type-B	Carbon emissions, manufacturing (kg of CO2e)	310
Number of upstream ports	1	Carbon emissions, logistics (kg of CO2e)	39
USB Type-A downstream ports quantity	4	Carbon emissions, energy usage (kg of CO2e)	83
VGA (D-Sub) ports quantity	1	Carbon emissions, end-of-life (kg of CO2e)	2
DVI port	✗	Total carbon emissions, w/o use phase (kg of CO2e)	351
HDMI *	✓	PAIA version	9/5/2018
HDMI ports quantity	1	Other features	
DisplayPorts quantity	1	Display	LED
Network		TV tuner integrated	✗
Wi-Fi	✗	Energy efficiency class (old)	A+
Ergonomics		Compliance industry standards	TCO
VESA mounting *	✓	Thin Client	
Panel mounting interface	100 x 100 mm	Thin client installed	✗
Cable lock slot *	✗		
Height adjustment *	✓		
Height adjustment	13 cm		
Pivot	✓		
Pivot angle	-90 - 90°		
Swivelling	✓		
Swivel angle range	-45 - 45°		
Tilt adjustment	✓		
Tilt angle range	-5 - 21°		



8592978429034



5397184200384

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.