

## StarTech.com 10G8A2CS-USB-C-HUB keskitin USB 3.2 Gen 2 (3.1 Gen 2) Type-C 10000 Mbit/s Harmaa

**Tuotemerkki :** StarTech.com

**Tuotekoodi:** 10G8A2CS-USB-C-HUB

**Tuotteen nimi :** 10G8A2CS-USB-C-HUB

StarTech.com 10G8A2CS-USB-C-HUB. Isäntäkoneen käyttöliittymä: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, Liittimiä: USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C. Tiedonsiirtonopeus: 10000 Mbit/s, Tuotteen väri: Harmaa, LED-merkivalot: Tila. Virtalähteen tyyppi: DC, Virrankulutus: 65 W, Tulojännite: 110 - 240 V. Tuotteen leveys: 80 mm, Tuotteen syvyys: 115 mm, Tuotteen korkeus: 30 mm. Pakkauksen leveys: 170 mm, Pakkauksen syvyys: 25 mm, Pakkauksen korkeus: 93 mm



<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C	Weight	287 g
Hub interfaces *	USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C	<b>Packaging data</b>	
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	8	Package width	170 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Package depth	25 mm
Ports quantity *	10	Package height	93 mm
DC-in jack	✓	Package weight	287 g
<b>Features</b>		<b>Packaging content</b>	
Data transfer rate *	10000 Mbit/s	AC adapter included	✓
Product colour	Grey	Included power plug types	EU, NA, UK
Overcurrent protection	✓	Cables included	USB Type-C to USB Type-C
LED indicators	Status	<b>Operational conditions</b>	
Cable jacket material	Thermoplastic elastomer (TPE)	Operating temperature (T-T)	0 - 50 °C
Cable length	1 m	Storage temperature (T-T)	-20 - 70 °C
<b>Power</b>		Operating relative humidity (H-H)	0 - 95%
Power supply type	DC	<b>Sustainability</b>	
Power consumption (typical)	65 W	Sustainability compliance	✓
Input voltage	110 - 240 V	<b>Logistics data</b>	
Output voltage	19 V	Master (outer) case width	272 mm
Output current	3.42 A	Master (outer) case length	380 mm
Power plug type	Type M	Master (outer) case height	272 mm
<b>Weight &amp; dimensions</b>		Products per master (outer) case	10 pc(s)
Width	80 mm	<b>Technical details</b>	
Depth	115 mm	Compliance certificates	CE, RoHS
Height	30 mm	<b>Other features</b>	
		Chipset	VIA - VL822-Q7, VIA - VL162



0065030899017



065030899017

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.