

## Allied Telesis 990-003868-80 Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta



**Tuotemerkki :** Allied Telesis

**Tuotekoodi:** AT-IE200-6GP

**Tuotteen nimi :** 990-003868-80

Allied Telesis 990-003868-80. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 4, USB 2.0 -porttien määrä: 1, Console-portti: RJ-45. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 12 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE.... Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki

Management features		Security	
Switch type *	Managed	Access Control List (ACL)	✓
Switch layer	L2	IGMP snooping	✓
Quality of Service (QoS) support	✓	SSH/SSL support	✓
Web-based management	✓	Authentication	MAC-based authentication
Ports & interfaces		Multicast features	
Basic switching RJ-45 Ethernet ports quantity *	4	Multicast support	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Design	
SFP module slots quantity	2	Rack mounting *	✗
Console port	RJ-45	Product colour	Black
USB 2.0 ports quantity	1	Power	
Power connector	DC-in jack	Input voltage	24 - 48 V
Network		Power consumption (max)	155 W
Networking standards *	IEEE 802.1Q, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Link aggregation	✓	Power over Ethernet plus (PoE+) ports quantity	4
MAC address auto-learning supported	✓	Operational conditions	
VLAN support	✓	Operating temperature (T-T)	-40 - 75 °C
Virtual LAN features	Port-based VLAN	Storage temperature (T-T)	-40 - 85 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage relative humidity (H-H)	5 - 95%
Data transmission		Weight & dimensions	
Switching capacity *	12 Gbit/s	Width	159 mm
MAC address table *	2000 entries	Depth	95 mm
Security		Height	95 mm
DHCP features	DHCP server, DHCP client	Weight	1.5 kg



0767035201900



767035201900

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.