QNAP QSW-IM1200-8C verkkokytkin Hallittu L2 musta

Tuotemerkki : QNAP

Tuotekoodi: QSW-IM1200-8C


Tuotteen nimi : QSW-IM1200-8C

QNAP QSW-IM1200-8C. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Console-portti: RS-232. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 240 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE.... DC-syöttöjännite: 9 - 54 V. Telineasennus



Management features		Design	
Switch type * Switch layer Quality of Service (QoS) support	Managed L2 ✔	Product colour Reset button LED indicators	Black ✓ Activity, Link, Power, Speed, Status
Web-based management	1	Electromagnetic compatibility	CLASS A
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports type *	×	Firmware upgradeable Fanless	1 1
Gigabit Ethernet (copper) ports quantity	1	Power	
Combo SFP ports quantity	8	Power source *	DC
SFP+ module slots quantity	4	Power supply included *	✓
Console port	RS-232	DC input voltage	9 - 54 V
Network		Power consumption (max)	78 W
Networking standards *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	×
		Operational conditions	
		Operating temperature (T-T)	-30 - 65 °C
10G support *	1	Operating relative humidity (H-H)	5 - 95%
Copper ethernet cabling technology	10GBASE-T, 100BASE-T, 1000BASE- LX, 1000BASE-SX, 1000BASE-T, 2500BASE-T	Weight & dimensions Width	285 mm
Full duplex		Depth	238 mm
Flow control support		Height	43.5 mm
Auto-negotiation		Weight	4.58 kg
VLAN support	· ·	Packaging content	
Data transmission		Cables included	AC
Switching capacity *	240 Gbit/s	Quick start guide	1
Throughput	120 Gbit/s	Packaging data	
MAC address table *	16000 entries	Rack rails	1
Jumbo frames support	1	Package weight	5.31 kg
Jumbo frames	9000	Certificates	5
Security		Certification	CE, FCC, VCCI, BSMI
DHCP features	DHCP client		

Security		Logistics data	
Access Control List (ACL)	✓	Harmonized System (HS) code	85176990
IGMP snooping	1		
Design			
Rack mounting *	 Image: A set of the set of the		



4713213519042

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.