

Allied Telesis FS710/24 Hallitsematon Fast Ethernet (10/100) Harmaa



Tuotemerkki : Allied Telesis

Tuotekoodi: AT-FS710/24-50

Tuotteen nimi : FS710/24

Allied Telesis FS710/24. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Fast Ethernet (10/100), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 4,8 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Seinäkiinnitteinen, Telineasennus

| Management features | | Design | |
|---|--|-----------------------------------|---|
| Switch type * | Unmanaged | Rack mounting * | ✓ |
| Ports & interfaces | | Product colour | Grey |
| Basic switching RJ-45 Ethernet ports quantity * | 24 | Wall mountable | ✓ |
| Basic switching RJ-45 Ethernet ports type * | Fast Ethernet (10/100) | Power | |
| Network | | AC input voltage | 100 - 240 V |
| Networking standards * | IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | AC input frequency | 50 - 60 Hz |
| 10G support * | ✗ | Power consumption (max) | 5.3 W |
| Copper ethernet cabling technology | 10BASE-T, 100BASE-TX | Power over Ethernet (PoE) | |
| Full duplex | ✓ | Power over Ethernet (PoE) * | ✗ |
| Flow control support | ✓ | Operational conditions | |
| Auto MDI/MDI-X | ✓ | Operating temperature (T-T) | 0 - 50 °C |
| Data transmission | | Storage temperature (T-T) | -25 - 70 °C |
| Switching capacity * | 4.8 Gbit/s | Operating relative humidity (H-H) | 5 - 90% |
| Throughput | 3.57 Mpps | Storage relative humidity (H-H) | 5 - 95% |
| MAC address table * | 8000 entries | Operating altitude | 0 - 2000 m |
| Jumbo frames support | ✓ | Weight & dimensions | |
| Jumbo frames | 2000 | Width | 305 mm |
| Packet forwarding rate (100 Mbps) | 148800 pps | Depth | 180 mm |
| Packet forwarding rate (10 Mbps) | 14880 pps | Height | 44 mm |
| Packet buffer memory | 0.256 MB | Weight | 1.6 kg |
| Security | | Certificates | |
| BPDU filtering/protection | ✓ | Certification | FCC 15 B / A, VCCI A, FCC A, EN55032 A, CISPR 32 A, RCM A, UL60950-1, CSA C22.2 No.60950-1, EN60950-1(TUV), CE RoHS |
| | | Logistics data | |
| | | Harmonized System (HS) code | 85176990 |



0767035211930



767035211930

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.