
## Allied Telesis

## Allied Telesis AT-GS910/5E-50 Unmanaged Gigabit Ethernet (10/100/1000) Grey

Brand : Allied Telesis

**Product code:** 990-004855-50



5 port 10/100/1000TX unmanaged switch with external power supply EU Power Adapter

Allied Telesis AT-GS910/5E-50 Unmanaged Gigabit Ethernet (10/100/1000) Grey:

The Allied Telesis GS910 Series offers unmanaged Gigabit switching solutions for the desktop, and small networks. The series has internal and external power supply versions, and also features network loop guard technology, which automatically detects any unexpected network loops, and prevents network devices from broadcast packet storms.

With minimal to no set-up, GS910 Series switches provide simple and seamless connectivity to existing network infrastructure. Each unmanaged switch is backed with a lifetime limited warranty. Allied Telesis AT-GS910/5E-50. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack

Management features		Data transmission	
Switch type *	Unmanaged	Packet forwarding rate (100 Mbps)	148800 pps
Ports & interfaces		Packet forwarding rate (10 Mbps)	14880 pps
Basic switching RJ-45 Ethernet ports 5		Security	
quantity * Basic switching RJ-45 Ethernet ports		Loop protection	1
type *	Gigabit Ethernet (10/100/1000)	BPDU filtering/protection	1
Gigabit Ethernet (copper) ports quantity	5	Design	
Power connector	DC-in jack	Rack mounting *	×
Network		Product colour	Grey
Networking standards *	IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Power	
		AC input voltage	100 - 240 V
10G support *	×	AC input frequency	50 - 60 Hz
Flow control support	1	Power consumption (max)	3.6 W
Broadcast storm control	1	Power over Ethernet (PoE)	
Cable length detection	1	Power over Ethernet (PoE) *	×
Data transmission		Operational conditions	
Throughput	10 Gbit/s 7.4 Mpps 2000 entries ✓ 1488000 pps	Operating temperature (T-T)	0 - 50 °C
		Weight & dimensions	
		Width	130 mm
		Depth	101 mm
		Height	30 mm
		Weight	720 g
		Logistics data	

Harmonized System (HS) code 85176990







767035207353

0767035207353

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.