

Allied Telesis AT-x230-10GT-50 Hallittu L3 Gigabit Ethernet (10/100/1000) Harmaa



Tuotemerkki : Allied Telesis

Tuotekoodi: 990-005392-50

Tuotteen nimi : AT-x230-10GT-50

Allied Telesis AT-x230-10GT-50. Kytin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 20 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Virtaliitin: DC-tulo jakkiliitin. Telineasennus

Management features		Design	
Switch type *	Managed	Rack mounting *	✓
Switch layer	L3	Stackable *	✓
Quality of Service (QoS) support	✓	Product colour	Grey
Web-based management	✓	LED indicators	✓
ARP inspection	✓	Safety	UL60950-1, CAN/CSA-C22.2 No. 60950-1-03, EN60950-1, EN60825-1, AS/NZS 60950.1
System event log	✓		
MIB support	✓		
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	8	Internal memory	256 MB
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Combo SFP ports quantity	2	AC input voltage	90 - 260 V
Power connector	DC-in jack	AC input frequency	47/63 Hz
Network		Power consumption (typical)	16 W
Networking standards *	IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✗
Port mirroring	✓	Operational conditions	
Full duplex	✓	Operating temperature (T-T)	0 - 50 °C
Flow control support	✓	Storage temperature (T-T)	-25 - 70 °C
Link aggregation	✓	Operating relative humidity (H-H)	5 - 90%
		Storage relative humidity (H-H)	5 - 95%
		Operating altitude	0 - 3048 m
		Heat dissipation	55 BTU/h
Data transmission		Weight & dimensions	
Switching capacity *	20 Gbit/s	Width	265 mm
Throughput	14.9 Mpps	Depth	180 mm
MAC address table *	16000 entries	Height	42.5 mm
		Weight	1.5 kg
Security		Packaging data	
DHCP features	DHCP server, DHCP client	Package width	430 mm
Access Control List (ACL)	✓	Package depth	360 mm
IGMP snooping	✓	Package height	150 mm
Security algorithms	802.1x RADIUS	Package weight	2.85 kg
Multicast features		Logistics data	
Multicast support	✓	Harmonized System (HS) code	85176990



0767035209630



767035209630

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.