

ZYXEL

Zyxel GS1915-24E Hallittu L2 Gigabit Ethernet (10/100/1000) 1U musta

Tuotemerkki : Zyxel

Tuotekoodi: GS1915-24E-EU0101F

Tuotteen nimi : GS1915-24E



Zyxel GS1915-24E. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE.... Seinäkiinnitteinen, Telineasennus, Kotelo: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2	Protocols	
Quality of Service (QoS) support	✓	Management protocols	SNMP v1, v2c, v3
Web-based management	✓	Design	
Cloud-managed	✓	Rack mounting *	✓
MIB support	✓	Form factor	1U
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports quantity *	24	LED indicators	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Wall mountable	✓
Network		Number of fans	0 fan(s)
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Performance	
10G support *	✗	Fanless	✓
Port mirroring	✓	Mean time between failures (MTBF)	674068 h
Flow control support	✓	Power	
Broadcast storm control	✓	Power source *	AC
Spanning tree protocol	✓	Power supply included *	✓
Ethernet LAN data rates	100,1000 Mbit/s	AC input voltage	100 - 240 V
VLAN support	✓	AC input frequency	50 - 60 Hz
Virtual LAN features	Port-based VLAN	Power consumption (max)	15.5 W
Data transmission		Power over Ethernet (PoE)	
Switching capacity *	48 Gbit/s	Power over Ethernet (PoE) *	✗
Forwarding rate	35.7 Mpps	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	10 - 95%

Data transmission		Operational conditions	
MAC address table *	8000 entries	Heat dissipation	53 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Jumbo frames	9000	Width	267 mm
Packet buffer memory	525 MB	Depth	162 mm
Security		Height	42 mm
DHCP features	DHCP client, DHCP relay	Weight	1.57 kg
IGMP snooping	✓	Packaging data	
Security algorithms	HTTPS, SHA-2, SSH-2, SSL/TLS	Package width	325 mm
SSH/SSL support	✓	Package depth	223 mm
Loop protection	✓	Package height	71 mm
Password protection	✓	Package weight	2.05 kg



4718937626786

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date