

ZYXEL

Zyxel GS1915-24EP Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : Zyxel

Tuotekoodi: GS1915-24EP-EU0101F

Tuotteen nimi : GS1915-24EP



Zyxel GS1915-24EP. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. MAC-osoitetaulukko: 8000 entries, Kytentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.1p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3at, IEEE.... Power over Ethernet -tuki. Seinäkiinnitteinen, Telineasennus, Kotelo: 1U

Management features		Protocols	
Switch type *	Managed	Management protocols	SNMP v1, v2c, v3
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Form factor	1U
Cloud-managed	✓	Product colour	Black
MIB support	✓	LED indicators	✓
Ports & interfaces		Wall mountable	✓
Basic switching RJ-45 Ethernet ports quantity *	24	Number of fans	0 fan(s)
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Network		Fanless	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.1p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az	MTBF (PoE)	768989 h
10G support *	✗	Power	
Port mirroring	✓	Power source *	AC
Flow control support	✓	Power supply included *	✓
Broadcast storm control	✓	AC input voltage	100 - 240 V
Spanning tree protocol	✓	AC input frequency	50 - 60 Hz
Ethernet LAN data rates	100,1000 Mbit/s	Power consumption (max)	166.1 W
VLAN support	✓	Power over Ethernet (PoE)	
Virtual LAN features	Port-based VLAN	Power over Ethernet (PoE) *	✓
Data transmission		Power over Ethernet (PoE) ports quantity	12
Switching capacity *	48 Gbit/s	Total Power over Ethernet (PoE) budget	130 W
Forwarding rate	35.7 Mpps	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-40 - 70 °C

Data transmission		Operational conditions	
MAC address table *	8000 entries	Operating relative humidity (H-H)	10 - 95%
Jumbo frames support	✓	Heat dissipation	566 BTU/h
Jumbo frames	9000	Weight & dimensions	
Security		Width	330 mm
DHCP features	DHCP relay, DHCP client	Depth	230 mm
IGMP snooping	✓	Height	44 mm
Security algorithms	HTTPS, SSH-2, SSL/TLS, SHA-2	Weight	2.48 kg
SSH/SSL support	✓	Packaging data	
Loop protection	✓	Package width	389 mm
Password protection	✓	Package depth	337 mm
Multicast features		Package height	79 mm
Multicast support	✓	Package weight	3.87 kg



4718937626823

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date