

ZYXEL

Zyxel XGS2220-54FP Hallittu L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki

Tuotemerkki : Zyxel

Tuotekoodi: XGS2220-54FP-EU0101F

Tuotteen nimi : XGS2220-54FP

Zyxel XGS2220-54FP. Kytin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48, Asennettujen SFP+ moduulien määrä: 4. MAC-osoitetaulukko: 32000 entries, Kytkentäkapasiteetti: 216 Gbit/s. Verkkostandardit: IEEE 802.3ab, IEEE 802.3bt, IEEE 802.1ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an,.... Power over Ethernet -tuki. Telineasennus



Management features		Protocols	
Switch type *	Managed	GARP VLAN Registration Protocol (GVRP)	✓
Switch layer	L3		
Quality of Service (QoS) support	✓		
ARP inspection	✓		
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	48	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)		
10G Ethernet (copper) ports quantity	2		
Installed SFP+ modules quantity *	4		
Network		Performance	
Networking standards *	IEEE 802.3ab, IEEE 802.3bt, IEEE 802.1ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an, IEEE 802.1p, IEEE 802.1s, IEEE 802.3x, IEEE 802.3at, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1w, IEEE 802.3az, IEEE 802.1x	Internal memory	1024 MB
10G support *	✓	Flash memory	64 MB
Routing entries	64	Mean time between failures (MTBF)	298.735 h
Data transmission		Power	
Switching capacity *	216 Gbit/s	Power source *	AC
Forwarding rate	161 Mpps	Power supply included *	✓
MAC address table *	32000 entries	AC input voltage	100 - 240 V
Jumbo frames support	✓	AC input frequency	50 - 60 Hz
Packet buffer memory	2 MB	Power consumption (max)	1161.6 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Power over Ethernet (PoE) ports quantity	50
		Total Power over Ethernet (PoE) budget	960 W
		Operational conditions	
		Operating temperature (T-T)	-20 - 50 °C
		Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	10 - 95%
		Storage relative humidity (H-H)	10 - 90%
		Heat dissipation	195.43 BTU/h

Security		Weight & dimensions	
DHCP features	DHCP relay, DHCP server	Width	441 mm
IGMP snooping	✓	Depth	330 mm
IGMP proxy	✓	Height	44 mm
Authentication type	IEEE 802.1x, RADIUS, TACACS+	Weight	5 kg
Multicast features			
Multicast Listener Discovery (MLD) snooping	MLD v1/v2		



4718937625130

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date