ATEN

ATEN CS1142D4C-AT-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CS1142D4C-AT-G

Tuotteen nimi : CS1142D4C-AT-G

ATEN CS1142D4C-AT-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DVI-I. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 3840 x 2160 pikseliä, Videokaistanleveys: 30 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli, Sertifiointi: 4K,NIAP,common_criteria,CC. Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz. Paino: 2,39 kg





2L-7D03UDX5,2L-7D02UDX3,2X-046G,2XRT-0019G

| Ports & interfaces | | Design | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Number of computers controlled * Keyboard port type * | | Push button Certification | ✓ 4K,NIAP,common_criteria,CC |
| Mouse port type *USBVideo port type *DVI-IDVI-I ports quantity4USB 2.0 Type-B ports quantity4Console ports *3.5mm headphone, DVI-I, USB AConsole USB ports quantity2Console DVI-I ports quantity2Audio connections✓ | | Display | |
| | | Built-in display * Power | × |
| | Power source Input voltage AC input frequency Input current | AC 100 - 240 V 50 - 60 Hz 1 A | |
| Headphone outputs RJ-11 ports quantity | • | Operational conditions Operating temperature (T-T) | 0 - 50 °C |
| PerformanceHD type *4K Ultra HDMaximum resolution *3840 x 2160 pixelsVideo bandwidth30 HzNumber of displays supported2 | | Storage temperature (T-T) Operating relative humidity (H- | -20 - 60 °C |
| | 30 Hz | Weight & dimensions Weight | 2.39 kg |
| Design | | Packaging data | |
| Rack mounting *✓Product colour *BlackHousing materialMetalLED indicators✓ | Package weight Packaging content | 3.03 kg | |
| | | Packaging content | 1x CS1142D4C 2-Port USB DVI Dual Display Secure KVM Switch with CAC 1x Power Cord 1x User Instructions |
| | | Other features | |
| | | I/O ports | USB CAC Port |

Compatibility



4710469341977

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.