


ASUS P12R-M/10G-2T/ASMB10 Intel C252 LGA 1200 (Socket H5) mikro ATX



Tuotemerkki : ASUS

Tuotekoodi: 90SB0AC0-M1UAY0

Tuotteen nimi : P12R-M/10G-2T/ASMB10

ASUS P12R-M/10G-2T/ASMB10. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1200 (Socket H5), Yhteensopivat prosessorit: Intel® Pentium®, Intel Xeon E. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 128 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III. Näytönohjainperhe: ASPEED, Näytönohjain: AST2600, Sisäisen näytönohjaimen muisti: 64 MB. Komponentti (tuotteelle): Palvelin, Emolevyn muototekijä: mikro ATX, Emolevyn piirisarjan perhe: Intel

Processor		Internal I/O	
Processor manufacturer *	Intel	Peripheral (Molex) power connectors (4-pin)	6
Processor socket *	LGA 1200 (Socket H5)	EPS power connector (8-pin)	✓
Compatible processor series *	Intel® Pentium®, Intel Xeon E	TPM connector	✓
Supported processor sockets	LGA 1700	Serial port headers	1
Memory		Rear panel I/O ports	
Supported memory types *	DDR4-SDRAM	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Number of memory slots *	4	Ethernet LAN (RJ-45) ports *	3
Memory slots type	DIMM	VGA (D-Sub) ports quantity *	1
Memory channels	Dual-channel	HDMI ports quantity *	1
Supported memory clock speeds	2666,2933,3200 MHz	Network	
Maximum internal memory *	128 GB	Ethernet LAN	✓
Supported memory module capacities	4GB, 8GB, 16GB, 32GB	Wi-Fi *	✗
Storage controllers		Features	
Supported storage drive interfaces *	M.2, SATA III	Motherboard chipset *	Intel C252
Graphics		Component for *	Server
Graphics card family	ASPEED	Motherboard form factor *	micro ATX
Graphics card	AST2600	Motherboard chipset family *	Intel
On-board graphics card memory	64 MB	Expansion slots	
Internal I/O		PCI Express x4 slots	1
USB 2.0 connectors *	1	PCI Express x16 (Gen 4.x) slots	1
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Number of M.2 (M) slots	1
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	2	Operational conditions	
Number of SATA III connectors *	6	Storage temperature (T-T)	-40 - 70 °C
ATX Power connector (24-pin)	✓	Operating temperature (T-T)	10 - 50 °C
Packaging data		Storage relative humidity (H-H)	20 - 90%
Weight & dimensions		Packaging data	
		Package weight	9.5 kg
		Weight & dimensions	
		Width	244 mm
		Depth	244 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date