



ASUS P12R-E/10G-2T/ASMB10 LGA 1200 (Socket H5) ATX

Tuotemerkki : ASUS

Tuotekoodi: 90SB0AI0-M1UAY0


Tuotteen nimi : P12R-E/10G-2T/ASMB10

ASUS P12R-E/10G-2T/ASMB10. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1200 (Socket H5), Yhteensopivat prosessorit: Intel® Pentium®, Intel Xeon E. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 128 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III. Näytönohjainperhe: ASPEED, Näytönohjain: AST2600, Sisältyvän näytönohjaimen malli: Aspeed AST2600. Ethernet-liitännän tyyppi: 10 Gigabit Ethernet, Nopea Ethernet, Gigabitti Ethernet, LAN-kontrolleri: Intel X710-AT2



Processor		Internal I/O	
Processor manufacturer *	Intel	Number of COM connectors	1
Processor socket *	LGA 1200 (Socket H5)	TPM connector	✓
Compatible processor series *	Intel® Pentium®, Intel Xeon E	Serial port headers	1
Memory		Rear panel I/O ports	
Supported memory types *	DDR4-SDRAM	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Number of memory slots *	4	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
Memory slots type	DIMM	Ethernet LAN (RJ-45) ports *	3
Memory channels	Dual-channel	PS/2 ports quantity	1
Supported memory clock speeds	2666,2933,3200 MHz	VGA (D-Sub) ports quantity *	1
Maximum internal memory *	128 GB	HDMI ports quantity *	1
Supported memory module capacities	8GB, 16GB, 32GB	Network	
Storage controllers		Ethernet LAN	✓
Supported storage drive interfaces *	M.2, SATA III	Ethernet interface type	10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet
Graphics		LAN controller	Intel X710-AT2
Parallel processing technology support *	Not supported	Wi-Fi *	✗
Graphics card family	ASPEED	Features	
Graphics card	AST2600	Component for *	Server
On-board graphics card model	Aspeed AST2600	Motherboard form factor *	ATX
On-board graphics card memory	64 MB	Motherboard chipset family *	Intel
Internal I/O		Expansion slots	
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	3	Number of M.2 (M) slots	2
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	2	Operational conditions	
Number of SATA III connectors *	8	Storage temperature (T-T)	-40 - 70 °C
ATX Power connector (24-pin)	✓	Operating temperature (T-T)	10 - 50 °C
		Storage relative humidity (H-H)	20 - 90%

Internal I/O		Packaging data	
Peripheral (Molex) power connectors (4-pin)	6	Package weight	1.3 kg
EPS power connector (8-pin)	✓	Weight & dimensions	
		Width	305 mm
		Depth	244 mm
		Other features	
		Weight	760 g



4711081420231

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date