ASUS PROART-RTX4080-16G NVIDIA GeForce RTX 4080 16 GB GDDR6X

Brand: ASUS **Product code**: 90YV0IX0-M0NB00

Product name: PROART-RTX4080-16G

- NVIDIA Ada Lovelace Streaming Multiprocessors: Up to 2x performance and power efficiency
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2x ray tracing performance
- Axial-tech fans scaled up for 21% more airflow
- 2.5-slot design: allows for greater build compatibility while maintaining premium cooling
- Dual Ball Fan Bearings last up to twice as long as conventional designs
- 0dB technology lets you enjoy light gaming in relative silence
- Auto-Extreme precision automated manufacturing for higher reliability
- GPU Tweak III profile Connect enables creators to seamlessly optimize system performance and cooling for every app

NVIDIA GeForce RTX 4080 16GB GDDR6X, PCI Express 4.0, OpenGL 4.6, 256-bit, 750W, 1 x 16-pin, 2.5 Slot





| Processor | | Performance | |
|--|---|---|-------------------------------------|
| CUDA * CUDA cores Graphics processor family * Graphics processor * Processor boost clock speed Processor frequency (OC mode) Maximum resolution * Parallel processing technology | 9728 NVIDIA GeForce RTX 4080 2505 MHz 2535 MHz 7680 x 4320 pixels Not supported | OpenGL version * HDCP HDCP version Dual Link DVI * NVIDIA G-SYNC NVIDIA Ansel | 4.6 ✓ 2.3 × ✓ |
| | | Design | |
| support * Maximum displays per videocard | 4 | Cooling type * Cooling technology | Active ASUS Axial-tech |
| Memory Discrete graphics card memory * Graphics card memory type * Memory bus * | 16 GB GDDR6X 256 bit 22.4 GB/s | Number of fans Number of slots Product colour | 3 fan(s) 2.5 Black, Gold |
| | | Power | |
| Memory bandwidth (max) Ports & interfaces | 22.4 GB/S | Minimum system power supply * Supplementary power connectors | 750 W 1x 16-pin |
| Interface type * HDMI ports quantity * HDMI version DisplayPorts quantity * DisplayPort version | PCI Express 4.0 1 2.1a 3 1.4a | Weight & dimensions Weight Length Depth Height | 1.1 kg 300 mm 50 mm 120 mm |
| | | Packaging content Manual | ✓ |





4711387183878

0197105183889



197105183889

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.