be quiet! System Power 10 virtalähdeyksikkö 850 W 20+4 pin ATX ATX musta

Tuotemerkki : be quiet! Tuotekoodi: BN330

Tuotteen nimi: System Power 10

be quiet! System Power 10. Kokonaisteho: 850 W, AC-syöttöjännite: 200 - 240 V, AC-syöttötaajuus: 50 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 55 cm, SATA-virtakaapelin pituus: 450,550,570,670,690,790 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 160 mm, Tuotteen syvyys: 86 mm, Tuotteen korkeus: 150 mm





| Power | | Performance | |
|--|--------------------------------------|-------------------------------------|---|
| Total power * | 850 W | Purpose * | PC |
| AC input voltage * | 200 - 240 V | Power supply unit (PSU) form factor | ATX |
| AC input frequency | 50 Hz | * | AIX |
| Input current | 5 A | ATX version | 2.52 |
| Power factor | 0.97 | EPS version | 2.92 |
| Power Factor Correction (PFC) type | Active | Noise level | 30.7 dB |
| Combined power (+3.3V) | 120 W | Bearing technology | Rifle |
| Combined power (+12V) | 849.6 W | Mean time between failures (MTBF) | 100000 h |
| Combined power (+5V) | 120 W | Certification | CB, TÜV, cRUus, cTUVus, RCM (Australia), BSMI, CU (Russia) |
| Combined power (-12V) | 3.6 W | Country of origin | Germany |
| Combined power (+5Vsb) Max output current (+3.3V) | 15 W 22 A | Design | |
| Max output current (+12V1) | 40 A | Product colour | Black |
| Max output current (+12V2) | 36 A | Cooling type | Active |
| Max output current (+12V2) | 22 A | Fan diameter | 12 cm |
| Max output current (+3V) | 0.3 A | Number of fans | 1 fan(s) |
| Max output current (+12V) | 3 A | Fan speed | 0 - 2000 RPM |
| Hold time | 17 ms | On/off switch | √ 2000 Kr M |
| Efficiency | 93.4% | On/on switch | • |
| Power Good signal delay range | 100 - 150 ms | Operational conditions | |
| Tower Good Signal delay runge | Over current, Over power, Over | Operating temperature (T-T) | 0 - 40 °C |
| Power protection features | voltage, Overheating, Short circuit, | Storage temperature (T-T) | -20 - 70 °C |
| | Under voltage | Operating relative humidity (H-H) | 0 - 90% |
| Ports & interfaces | | Storage relative humidity (H-H) | 0 - 95% |
| Motherboard power connector * | 20+4 pin ATX | Weight & dimensions | |
| Motherboard power cable length | 55 cm | Width | 160 mm |
| Number of SATA power connectors | 6 | Depth | 86 mm |
| Number of PATA power connectors | 1 | Height | 150 mm |
| SATA power cable length | 450,550,570,670,690,790 mm | Weight | 2.14 kg |
| Peripheral (Molex) power connectors (4-pin) * | 1 | Packaging data | |
| Peripheral (Molex) power cable length | 790 mm | Manual | ✓ German, English, Spanish, French, |
| EPS power connector (8-pin) | ✓ | Manual languages | Polish, Russian |
| PCI Express power connectors (6+2 pin) | 4 | Package width Package depth | 220 mm 300 mm |
| | | | |

| Ports & interfaces | | Packaging data | |
|--------------------------------|--------------|------------------------------------|---|
| PCI Express power cable length | 65 cm | Package height | 100 mm |
| CPU power connector (4+4 pin) | ✓ | Package weight | 2.6 kg |
| CPU power cable length | 60 cm | Technical details | |
| ATX power connector (20+4 pin) | ✓ | Sustainability certificates | ENERGY STAR, ErP |
| PCI Express connector | ✓ | Warranty period | 5 year(s) |
| Cabling type | Non-Modular | Compliance certificates | CCC, CE, Federal Communications Commission (FCC), RoHS, WEEE |
| Performance | | | Commission (FCC), Norts, WEEL |
| 80 PLUS certification * | 80 PLUS Gold | Other features | |
| | | Screws included | ✓ |
| | | Noise level (silent mode, <30%) | 10.3 dB |
| | | Noise level (quiet mode, 50%) | 10.4 dB |
| | | Noise level (full-load mode, 100%) | 30.7 dB |



4260052189108

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.