Chieftec Smart GPS-700A8 power supply unit 700 W 20+4 pin ATX PS/2 Black

Brand : Chieftec Product family: Smart Product code: GPS-700A8

Product name: GPS-700A8

Chieftec Smart Series GPS-700A8, 700W, ATX, 85% Efficiency

Chieftec Smart GPS-700A8 power supply unit 700 W 20+4 pin ATX PS/2 Black:

The smart series offers both quality and efficiency. The PSU itself is painted in decent black, equipped with long native cables, a power cord, and a solid carton to protect it. With an efficiency of over 80%, the SMART SERIES fulfills the requirement of green power at an attractive price.

Chieftec Smart GPS-700A8. Total power: 700 W, AC input voltage: 230 V, Power Factor Correction (PFC) type: Active. Motherboard power connector: 20+4 pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: PS/2. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 87 mm





| _ | | | |
|---|--|-------------------------------------|-------------|
| Power | | Ports & interfaces | |
| Total power * | 700 W | EPS power connector (8-pin) | ✓ |
| AC input voltage * | 230 V | PCI Express power connectors (6+2 | 2 |
| Power factor | 0.9 | pin) | _ |
| Power Factor Correction (PFC) type | Active | Floppy drive power connector | 1 |
| Combined power (-12V) | 3.6 W | Cabling type | Non-Modular |
| Combined power (+5Vsb) | 12.5 W | Performance | |
| Max output current (+3.3V) | 22 A 54 A 22 A | 80 PLUS certification * | No |
| Max output current (+12V1) | | Purpose * | PC |
| Max output current (+5V) | | Power supply unit (PSU) form factor | DC /2 |
| Max output current (-12V) | 0.3 A | * | PS/2 |
| Max output current (+5Vsb) | 2.5 A | ATX version | 2.3 |
| Efficiency | 80% | Design | |
| Power protection features | Over voltage, Overload, Short circuit, Under voltage | Product colour | Black |
| Ports & interfaces | | Cooling type | Active |
| | 20.4.1.4.7.4 | Fan diameter | 12 cm |
| Motherboard power connector * | 20+4 pin ATX | Number of fans | 1 fan(s) |
| Number of SATA power connectors Peripheral (Molex) power connectors (4-pin) * | 62 | Weight & dimensions | |
| | | Width | 150 mm |
| | | Depth | 140 mm |
| | | Height | 87 mm |
| | | Weight | 1.62 kg |



4710713239579

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.