

REDUNDANT

MRG-5700V // SLEEVED // 700WATT



Product: PSU

Form factor: PSII

Color: silver

If you are looking for "green-power" and high-performance 24-7, then the MRG-5700V will be the choice.

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: >80%

Dimensions (DxWxH): 210mm x 150 mm x 87 mm

PCF: Active PFC (0,9)

Fan: 40mm fan (2x 40mm per module)

Connectors

2+4 PIN	8PIN EPS	System LED	SATA	Molex	Floppy	TTL Signal Kabel	Buzzer
1	1	1	6	5	1	1	1
8PIN EPS (4+4)	6PIN PCIe	8 PIN PCIe (6+2)					
1	1	1					

DC Output / AC Input

AC INPUT: 100V / 9A 240V / 5A FREQUENCY: 47 - 63 HZ MAX. LOAD: 700W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	-5V	P.F.	-12V	+5VSB
	32A	32A	57A	N/A	N/A	N/A	>0,9	0,8A	3,5A
	190W		N/A						

Security:

Met.al frame, 2x 700W modules, TTL-Signal, Buzzer- LED Alarm, hot-swap, hot-plug features, full range Input 100V~240V, Meet FCC, CISPR EMI regulation, Balanced load sharing design, UVP; OVP; SCP; OPP; OCP; OTP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.