

## Chieftec MRZ 800W virtalähdeyksikkö 1600 W 20+4 pin ATX PS/2 mini Metallinen

**Tuotemerkki :** Chieftec

**Tuotekoodi:** MRZ-5800K2V

**Tuotteen nimi :** MRZ 800W

Chieftec MRZ 800W. Kokonaisteho: 1600 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 55 cm, SATA-virtakaapelin pituus: 200,550 mm. Tarkoitus: Palvelin, Virransyöttöyksikön mitat: PS/2 mini, 80 PLUS certification: 80 PLUS Platinum. Tuotteen väri: Metallinen, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 4 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 222 mm, Tuotteen korkeus: 86 mm



<b>Power</b>		<b>Ports &amp; interfaces</b>	
Total power *	1600 W	PCI Express power cable length	55 cm
AC input voltage *	100 - 240 V	Floppy disk drive connector	✓
AC input frequency	47 - 63 Hz	Floppy disk drive cable length	55 cm
Input current	6 - 10 A	<b>Performance</b>	
Power factor	0.9	80 PLUS certification *	80 PLUS Platinum
Combined power (+3.3V)	165 W	Purpose *	Server
Max output current (+3.3V)	20 A	Power supply unit (PSU) form factor *	PS/2 mini
Max output current (+12V)	66 A	ATX version	2.3
Max output current (+5V)	20 A	<b>Design</b>	
Max output current (-12V)	0.5 A	Product colour	Metallic
Max output current (+5Vsb)	3.5 A	Cooling type	Active
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Fan diameter	4 cm
<b>Ports &amp; interfaces</b>		Number of fans	2 fan(s)
Motherboard power connector *	20+4 pin ATX	<b>Weight &amp; dimensions</b>	
Motherboard power cable length	55 cm	Width	150 mm
Number of SATA power connectors	4	Depth	222 mm
SATA power cable length	200,550 mm	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	2	Weight	5.2 kg
Peripheral (Molex) power cable length	200,550 mm	<b>Packaging data</b>	
EPS power connector (8-pin)	✓	Package weight	5.7 kg
EPS power connector (4+4 pin)	✓	<b>Technical details</b>	
PCI Express power connectors (6+2 pin)	6	Compliance certificates	RoHS
<b>Other features</b>		EPS cable length	55 cm
		Mounting type	Rack mounting

#### Other features

Redundant power supply (RPS) support ✓



0753263076687



753263076687

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.