## EPSON

## Epson EB-770Fi data projector Ultra short throw projector 4100 ANSI lumens 3LCD 1080p (1920x1080) White

Brand : Epson

Product code: V11HA78080

Product name : EB-770Fi

EB-770Fi

Epson EB-770Fi data projector Ultra short throw projector 4100 ANSI lumens 3LCD 1080p (1920x1080) White:

## Agile USTi laser display

Project your vision, with a Full HD interactive large screen display up to 100" that will enhance engagement, learning and productivity.

Whatever the size of class or meeting room, unrestricted and interactive learning sessions are possible with this bright, compact and affordable touch-display solution.

The EB-770Fi's bright image, scalable up to 100", is clearly visible from every angle and at a distance, and content can easily be shared or streamed directly from multiple devices for the ultimate collaborative experience.





| Projector  |   | Network                           |                                    |
|--|---|-----------------------------------|------------------------------------|
| Screen size compatibility * 1524 - 254                                   | 1524 - 2540 mm (60 - 100")                | Ethernet LAN data rates           | 10,100 Mbit/s                      |
| Projector brightness *   | 4100 ANSI lumens                          | Wi-Fi *                           | 1                                  |
| Projection technology *  | 3LCD                                      | Wi-Fi standards                   | 802.11a, 802.11b, 802.11g, Wi-Fi 4 |
| Projector native resolution *  | 1080p (1920x1080)                         |                                   | (802.11n), Wi-Fi 5 (802.11ac)      |
| Contrast ratio (typical) *<br>Native aspect ratio *<br>Number of colours | 2500000:1<br>16:9<br>1.07 billion colours | Storage                           |                                    |
|  |   | Card reader integrated *          | ×                                  |
| Vertical scan range  | 192 - 240 Hz                              | Features                          |                                    |
| Keystone correction, horizontal  | -3 - 3°                                   | Interactive *                     | 1                                  |
| Keystone correction, vertical  | -3 - 3°                                   | Interactive input supported       | Interactive pen/Touch              |
| Heat dissipation   | 895 BTU/h                                 | Noise level (economic mode)       | 27 dB                              |
| Light source   |   | Noise level *                     | 37 dB                              |
| Light source type *  | Laser                                     | Multimedia                        |                                    |
| Service life of light source *   | 20000 h                                   | Built-in speaker(s) *             | 1                                  |
| Service life of light source<br>(economic mode)                          | 30000 h                                   | RMS rated power                   | 16 W                               |
| Lens system  |   | Design                            |                                    |
| -  | Manual                                    | Market positioning *              | Presentation                       |
| Focus *<br>Fixed focal length  | Manual<br>3.7 mm                          | Product type *                    | Ultra short throw projector        |
| Frumber (relative aperture)  | 1.6                                       | Product colour *                  | White                              |
| Zoom capability  |   | Placement                         | Ceiling, Desktop, Wall             |
| Zoom ratio   | 1.35:1                                    | Cable lock slot                   | 1                                  |
| Throw ratio  | 0.25 - 0.35:1                             | Cable lock slot type              | Kensington                         |
| Video  |   | Power                             |                                    |
| Analog signal format system *  | Not supported                             | Power source *                    | AC                                 |
| Full HD *  |   | Power consumption (typical) *     | 197 W                              |
| 3D *   | ×   | Power consumption (standby) $st$  | 0.5 W                              |
|  | ×   | Power consumption (PowerSave)     | 199 W                              |
| Ports & interfaces   |   | AC input frequency                | 50/60 Hz                           |
| USB 2.0 ports quantity   | 4   | AC adapter output voltage         | 100 - 240 V                        |
| USB 2.0 Type-A ports quantity  | 2   | Operational conditions            |                                    |
| USB 2.0 Type-B ports quantity  | 2   | Storage temperature (T-T)         | -10 - 60 °C                        |
| Microphone in  | ✓   | Operating relative humidity (H-H) | 20 - 80%                           |
| Serial interface type *  | RS-232C                                   | Storage relative humidity (H-H)   | 10 - 90%                           |

| Ports & interfaces           |   | Weight & dimensions       |         |
|------------------------------|---|---------------------------|---------|
| VGA (D-Sub) ports quantity * | 2 | Width                     | 356 mm  |
| HDMI ports quantity *        | 3 | Depth                     | 395 mm  |
| DVI port *                   | × | Height                    | 133 mm  |
| Network                      |   | Weight *                  | 6 kg    |
| Ethernet LAN *               | 1 | Packaging content         |         |
| Ethernet LAN (RJ-45) ports   | 1 | Remote control included * | 1       |
|                              |   | Batteries included        | 1       |
|                              |   | Cables included           | AC, USB |



8715946715230

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.