Shuttle

Shuttle DS20U7V2 barebone-tietokonerunko 1.3L kokoinen PC musta i7-10510U Intel $\$ SoC 1,8 GHz

Tuotemerkki : Shuttle

Tuotekoodi: DS20U7V2

Tuotteen nimi : DS20U7V2

Shuttle DS20U7V2. Alustatyyppi: 1.3L kokoinen PC, Tuotetyyppi: Mini PC Barebone. Emolevyn piirisarja: Intel® SoC, BIOS-tyyppi: UEFI AMI. Tuetut muistityypit: DDR4-SDRAM, Muistipaikkojen lukumäärä: 2, Sisäinen enimmäismuisti: 64 GB. Tuetut tallennusasematyypit: HDD & SSD, Tallennuslaitteen liitäntä: PCI Express, Serial ATA III. Ethernet LAN (RJ-45) -portit: 2. Jäähdytyksen tyyppi: Passiivinen. Virtalähde: 65 W





| Processor | | Design | |
|---|--|--|---|
| Processor manufacturer Processor family Processor generation Processor model Processor cores Processor threads Processor threads Processor boost frequency Processor frequency Built-in processor * Processor lithography Processor cache Thermal Design Power (TDP) CPU configuration (max) | Intel Intel® Core™ i7 10th gen Intel® Core™ i7 i7-10510U 4 8 4.9 GHz 1.8 GHz ✓ 14 nm 8 MB 15 W 1 | LED indicators Cable lock slot Cable lock slot type VESA mounting Product type * Performance Motherboard chipset Number of processors supported BIOS type Trusted Platform Module (TPM) Trusted Platform Module (TPM) | HDD, Power Kensington Mini PC barebone Intel SoC 1 UEFI AMI 2.0 |
| Memory | | Processor special features | |
| Memory slots type * Number of memory slots * Maximum internal memory Supported memory clock speeds Supported memory types Memory channels Memory voltage Non-ECC | SO-DIMM 2 64 GB 2666 MHz DDR4-SDRAM Dual-channel 1.2 V ✓ | Embedded options available Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT) Intel 64 Idle States Enhanced Intel SpeedStep Technology Intel Flex Memory Access | × ✓ ✓ ✓ ✓ ✓ ✓ |

| Storage | | Processor special features | |
|--|---------------------------------|--|--|
| Supported storage drive types * | HDD & SSD | Intel Trusted Execution Technology | × |
| Storage drive sizes supported * | 2.5,M.2 | Execute Disable Bit | ~ |
| Storage drive interface | PCI Express, Serial ATA III | Intel TSX-NI | × |
| Number of storage drives supported | 2 | Intel Stable Image Platform Program | |
| Card reader integrated | 1 | (SIPP) | × |
| Compatible memory cards | SD, SDHC, SDXC | Intel Clear Video Technology | Image: A set of the set of the |
| Graphics | | Intel Virtualization Technology (VT- x) | 1 |
| On-board graphics card st | 1 | | |
| Graphics card family | Intel | Logistics data | |
| On-board graphics card model | Intel [®] UHD Graphics | Harmonized System (HS) code | 84733080 |
| Audio | | Software | |
| Built-in speaker(s) * | × | Windows operating systems supported | Windows 10, Windows 11 |
| Network | | Linux operating systems supported | 1 |
| Ethernet LAN * | 1 | Operating system installed | × |
| Wi-Fi * | × | Power | |
| LAN controller | Intel® I211, Intel® I219 | Power supply type * | External AC adapter |
| Ports & interfaces | | Power supply | 65 W |
| USB 2.0 ports quantity * | 4 | Number of power supply units | 1 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 2 | AC input voltage | 100 - 240 V |
| ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A | | AC input frequency | 50 - 60 Hz |
| ports quantity | 2 | AC adapter output voltage AC adapter output current | 19 V 3.42 A |
| HDMI ports quantity * | 1 | | J.42 A |
| HDMI version | 2.0a | Operational conditions | |
| VGA (D-Sub) ports quantity * | 1 | Operating temperature (T-T) | 0 - 40 °C |
| DisplayPorts quantity DisplayPort version | 1 1.2 | Operating relative humidity (H-H) | 10 - 90% |
| Microphone in | 1.2 | Weight & dimensions | |
| Headphone outputs | 1 | Width | 165 mm |
| Ethernet LAN (RJ-45) ports * | 2 | Depth Height | 200 mm 39.5 mm |
| Serial ports quantity | 1 | Weight | 1.5 kg |
| DC-in jack | 1 | Package weight | 2.2 kg |
| Expansion slots | | Packaging content | |
| PCI Express slots version | 3.0 | Power cord included | 1 |
| Number of M.2 (M) slots | 1 | AC adapter included | 1 |
| Design | | Quick start guide | ✓ |
| Chassis type * | 1.3L sized PC | Drivers included | Image: A second s |
| Product colour * | Black | Other features | |
| Cooling type * | Passive | Country of origin | China |
| On/off switch | ✓ | ; | |





887993005362

0887993005362

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.