

HyperDrive Next

HD4002GL

6 Port USB-C Hub

Dimensions:

Length x Width x Height (cm) - 11.5 x 3.7 x 1.5 cm

Weight (kg) - Approx. 0.069 Kg

SRP: £64.99 | €72.99



Product Specification – HD4002GL

Connection to host device

Connector type	USB-C*
Connector technology	USB 3.2 Gen 2 (10 Gbps)
Graphics Technology	DP Alt Mode

Host device port compatibility

USB 3	●
USB4	●
Thunderbolt 3	●
Thunderbolt 4	●

Video ports

HDMI	1x HDMI 2.0
Display Port	--
VGA	--
Video via High-speed USB / Thunderbolt port	--
Maximum no. of monitor(s)	1
Maximum resolution (single monitor)	4K @ 60 Hz**
Maximum resolution (multi-monitor)	--
HDR via HDMI	--

Connection Ports

USB-A (Power / Max data speed)	2x USB 3.2 Gen2 (10 Gbps)
USB-C (Power / Max data speed)	1x USB PD 3.0 (Max. 100 W)
Thunderbolt 3	--
Thunderbolt 4	--
RJ45 Ethernet	--
3.5 mm Audio	--
Other audio ports	--
Memory cards	SD 4.0 (312 MB/s) - UHS-II card compatible*****

Power

USB Power Delivery to host device	● - when hub is connected to optional USB-C PD 3.0 charger
Max. PD power / PD pass through to host	Max. 100 W PD 3.0 / up to 85 W pass through to host device***

Recommended USB-C chargers

Hyper HJG100 100 W GaN charger	●
Hyper HJG140 140 W Universal GaN charger	●
Targus APA108 100 W laptop charger	●

Host device system OS compatibility

Works with Windows®	●
Works with MacOS®	●
Works with ChromeOS®	●
Works with iOS®	●****
Works with Android®	●
Works with Samsung DEX	●
Works With Linux Ubuntu™	--

Device compatibility

Windows® Laptop	●
Microsoft Surface® Laptop	●
ChromeBook®	●
Apple iMac®	●
Apple MacBook Pro® / Air® 2016 - 2019	●
Apple MacBook Pro® / Air® M1 / M2 2020 - 2022	●
Apple MacBook Pro® / M1 / M2 Pro / Max 2021 - 2023	●
Apple iPad Pro® 2018 or later	●****
Apple iPad Air® 2020 or later	●****
Android® Tablet	●
Android® Smartphone	●

Other features

Construction material	Yes - with 100% recycled Aluminium and up to 85% PCR plastics where applicable
USB-C cable to host device	Built in cable to host device
Warranty	2 years

Content

What's in the box	● HD4002GL HyperDrive NEXT 6 port USB-C Hub ● User Guide
-------------------	---

Notes

*Full hub data, video and power functionality will require host device with USB-C port compatible with DP Alt Mode, Power Delivery PD 3.0 and USB 3.2 Gen 1/ Gen 2
 **4K 60 Hz video required host device USB-C port compatible with DP1.4
 *** when using optional 100 W USB-C PD 3.0 charger
 **** Compatible with iPad® with USB-C/ Thunderbolt™ port. Using extended mode onto external monitor requires iPadOS 16 or later
 ***** Maximum SD 4.0 transfer speed requires UHS-II compliant SD cards. Actual transfer speed depends SD card read and write speed specifications and host device processor and port capability.