# ASUS M5A78L-M LX3 AMD 760G Socket AM3+ mikro ATX

Tuotemerkki : ASUS   **Tuotekoodi:** 90-MIBI40-G0EAY0GZ

Tuotteen nimi : M5A78L-M LX3

ASUS M5A78L-M LX3. Suoritinvalmistaja: AMD, Prosessorin kanta: Socket AM3+, Yhteensopivat prosessorit: AMD Phenom. Tuetut muistityypit: DDR3-SDRAM, Sisäinen enimmäismuisti: 16 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: SATA, SATA II, RAID-tasot: 0, 1, 10, JBOD. Tuettu rinnakkaiskäsittelyteknologia: Hybrid CrossFireX, Näytönohjaimen enimmäismuisti: 1024 MB, Näytönohjainperhe: ATI. Ethernet-liitännän tyyppi: Gigabitti Ethernet, Verkko-ominaisuudet: Gigabit Ethernet

Processor

Processor manufacturer *	AMD
Processor socket *	Socket AM3+
Compatible processor series *	AMD Phenom
Processor thermal power (max)	95 W

Memory

Supported memory types *	DDR3-SDRAM
Number of memory slots *	2
Memory slots type	DIMM
Memory channels	Dual-channel
ECC compatibility	Non-ECC
Supported memory clock speeds	1066,1333,1600,1866 MHz
Maximum internal memory *	16 GB
Unbuffered memory	✔

Storage controllers

Supported storage drive interfaces *	SATA, SATA II
RAID levels	0, 1, 10, JBOD

Graphics

Maximum graphics card memory	1024 MB
Parallel processing technology support *	Hybrid CrossFireX
On-board graphics card	✔
Graphics card family	ATI
Graphics card	Radeon HD 3000
Maximum resolution	2560 x 1440 pixels
DirectX version	10
Discrete graphics support	✘

Rear panel I/O ports

Ethernet LAN (RJ-45) ports *	1
PS/2 ports quantity	2
VGA (D-Sub) ports quantity *	1
Headphone outputs	1
Microphone in	✔
COM ports quantity	1

Network

Ethernet LAN	✔
Ethernet interface type	Gigabit Ethernet
Wi-Fi *	✘
Bluetooth	✘
Networking features	Gigabit Ethernet

Features

Motherboard chipset *	AMD 760G
Motherboard southbridge	AMD SB710
Audio chip	Realtek ALC887
Audio output channels *	7.1 channels
Component for *	PC
Motherboard form factor *	micro ATX
Motherboard chipset family *	AMD
Power source type	ATX

Expansion slots

PCI Express x1 slots	1
PCI Express x16 slots	1
PCI slots	1
PCI Express slots version	2.0

Internal I/O

USB 2.0 connectors *	2
Number of SATA II connectors	4
Front panel audio connector	✔
ATX Power connector (24-pin)	✔
Number of EATX power connectors	1
CPU fan connector	✔
Chassis intrusion connector	✔

Rear panel I/O ports

USB 2.0 ports quantity *	4

BIOS

BIOS type *	AMI
BIOS memory size	16 Mbit
ACPI version	2.0a

Weight & dimensions

Width	244 mm
Depth	188 mm

Packaging content

Cables included	SATA
Drivers included	✔

Other features

S/PDIF in port	✘
Controller interface type	AMD SB710
PCI Express slots quantity	2

||||||||||||||||||||||||||||||||||||||||||||||||||||

4719543185049

||||||||||||||||||||||||||||||||||||||||||||||||||||

4719543185469

||||||||||||||||||||||||||||||||||||||||||||||||||||

5054484780977