

EZVIZ H6c 2K+ Kuutio IP-turvakamera Sisätila 2560 x 1440 pikseliä Vastaanotto

Tuotemerkki: EZVIZ Tuotekoodi: CS-H6C-R100-8B4WF

Tuotteen nimi: H6c 2K+

EZVIZ H6c 2K⁺. Malli: IP-turvakamera, Tuettu sijoitus: Sisätila, Yhteysteknologia: Langallinen & langaton. Kiinnitystyyppi: Vastaanotto, Tuotteen väri: Valkoinen, Kotelo: Kuutio. Objektiivin kuvakulma, vaakasuora: 75°, Objektiivin kuvakulma, pystysuora: 45°, Objektiivin kuvakulma, kulmittain: 85°. Anturin tyyppi: CMOS, Optisen sensorin koko: 25,4 / 3 mm (1 / 3"). Linssin halkaisija: 4 mm



| Performance | | Network | |
|--|---|---|---|
| Type * Placement supported * Connectivity technology * Auto-tracking Infrared (IR) cut-off filter | IP security camera Indoor Wired & Wireless ✓ | Wi-Fi * Wi-Fi standards Wi-Fi data rate (max) Bluetooth * Channel bandwidth | 802.11b, 802.11g, Wi-Fi 4 (802.11n) 72 Mbit/s X 20 MHz |
| Certification | CE / UL / FCC / WEEE / REACH / RoHS / UKCA | Storage | |
| Design Form factor * Mounting type * Product colour * | Cube Desk White | Built-in HDD * Card reader integrated Compatible memory cards Maximum memory card size | X ✓ MicroSD (TransFlash) 256 GB |
| Camera | Willie | Ports & interfaces | |
| Camera tilt control | ✓ | Ethernet LAN (RJ-45) ports | 1 |
| Lens viewing angle, horizontal Lens viewing angle, vertical Lens viewing angle, diagonal | 75° 45° 85° | Security Security algorithms | 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK |
| Image sensor | | Power | |
| Optical sensor size Sensor type * | 25.4 / 3 mm (1 / 3") CMOS | Power source type * Power consumption (max) DC output voltage | DC 5 W 5 |
| Lens system Lens diameter | 4 mm | DC output current | 1 A |
| Night vision | 4 (1)(1) | Operational conditions | |
| Night vision * Night vision distance | ✓ 10 m | Operating temperature (T-T) Weight & dimensions Width | -10 - 45 °C 88.2 mm |
| Video Maximum resolution * Total megapixels * Video compression formats Digital Wide Dynamic Range | 2560 x 1440 pixels 4 MP H.264, H.265 | Depth Height Weight Packaging data | 88.2 mm 119 mm 218 g |
| (DWDR) | ✓ | Package width Package depth | 103 mm 103 mm |
| Network | | Package height | 186 mm |
| Ethernet LAN * Ethernet interface type | ✓ Fast Ethernet | Packaging content Number of cameras * Screws included Drilling template included | 1 |



6941545615035

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.