

Brother RJ-3050 POS printer 203 x 200 DPI Wired & Wireless Direct thermal Mobile printer

Brand : Brother

Product code: RJ-3050

Product name : RJ-3050

RJ-3050 3" Portable Printer + Bluetooth, 32MB, ZPL II, CPCL, 750g

Brother RJ-3050. Print technology: Direct thermal, Type: Mobile printer, Maximum resolution: 203 x 200 DPI. Maximum printing width: 7.2 cm, Maximum media length: 100 cm. Connectivity technology: Wired & Wireless, Bluetooth version: 2.1+EDR, Bluetooth profiles: OPP, SPP. Wi-Fi standards: 802.11b, 802.11g, Wi-Fi 4 (802.11n). Built-in barcodes: GS1 DataBar Limited, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN128,..., Internal memory: 32 MB, Page description languages: CPCL-native, ESC P



Printing		Power	
Maximum resolution	203 x 200 DPI	Power source type *	AC, Battery
Print speed	127 mm/sec	Battery technology	Lithium-Ion (Li-Ion)
Print technology *	Direct thermal	Power supply type	AC
Type *	Mobile printer	System requirements	
Paper handling		Compatible operating systems	Windows 8, 7, Vista, Server 2012 R2, Server 2012, Server 2008 R2, Server 2008
Maximum printing width	7.2 cm	Weight & dimensions	
Maximum media length	100 cm	Width	113 mm
Ports & interfaces		Depth	80 mm
USB port *	✓	Height	186 mm
USB 2.0 ports quantity	1	Weight	610 g
Bluetooth	✓	Packaging data	
Bluetooth version	2.1+EDR	Bundled software	SDK (Software Development Kit)
Connectivity technology *	Wired & Wireless	Packaging content	
Bluetooth profiles	OPP, SPP	Quick start guide	✓
Standard interfaces	Bluetooth, USB 2.0, Wireless LAN	Batteries included	✓
Network		Print quality	
Ethernet LAN *	✗	Maximum print height	7.2 cm
Wi-Fi *	✓	Logistics data	
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Harmonized System (HS) code	84433210
Features		Other features	
Built-in barcodes *	GS1 DataBar Limited, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN128, EAN13, EAN8, GS1 DataBar, GS1-128, ITF-25, MaxiCode, Micro QR Code, PDF417, POSTNET, QR Code, UPC-A, UPC-E	LED indicators	✓
Page description languages	CPCL-native, ESC P	International Protection (IP) code	IP54
		Battery type	PA-BT-001-B

Features

Internal memory *	32 MB
Flash memory	32 MB

Design

Product colour *	Black
------------------	-------



4977766741187

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date