

StarTech.com SV231DPU34K KVM-kytkin musta

Tuotemerkki : StarTech.com

Tuotekoodi: SV231DPU34K

Tuotteen nimi : SV231DPU34K

StarTech.com SV231DPU34K. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 3840 x 2160 pikseliä, Käyttäjien määrä: 1 käyttäjä (t). Tuotteen väri: musta, Kotelon materiaali: Terästä, Keskimääräinen vikaantumisaika: 60000 h. Tulojännite: 100 - 240 V, Syöttöjännite: 0.6 A, Ulostulojännite: 12 V. Vaatimustenmukaisuustodistukset: RoHS



Ports & interfaces		Power	
Number of computers controlled *	2	Input current	0.6 A
Keyboard port type *	USB	Output voltage	12 V
Mouse port type *	USB	Output current	1.5 A
Video port type *	DisplayPort	Power consumption (typical)	18 W
DisplayPorts quantity	3	External power adapter	✓
DisplayPort version	1.2	Power plug type	Type M
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	2	Compatible power plug types	AU, EU, JP, UK, US
Console ports *	3.5mm headphone, DisplayPort, USB A	Sustainability	
Console USB ports quantity	6	Compliance certificates	RoHS
USB connector type	USB Type-A, USB Type-B	Operational conditions	
Audio connections	✓	Operating temperature (T-T)	0 - 40 °C
Headphone outputs	3	Storage temperature (T-T)	-10 - 60 °C
DC-in jack	✓	Operating relative humidity (H-H)	0 - 80%
Performance		Weight & dimensions	
HD type *	4K Ultra HD	Width	160 mm
Maximum resolution *	3840 x 2160 pixels	Depth	100 mm
HDCP	✓	Height	40 mm
Daisy chain	✗	Weight	1.1 kg
Number of users	1 user(s)	Packaging data	
Audio channels	2.0	Package width	189 mm
Design		Package depth	238 mm
Product colour *	Black	Package height	91 mm
Housing material	Steel	Packaging content	
LED indicators	✓	Quick installation guide	✓
Hot keys	✓	AC adapter included	✓
Mean time between failures (MTBF)	60000 h	Rubber feet	✓

Design		Other features	
Certification	CE, FCC, TAA, REACH	IP control	✘
Display		Logistics data	
Built-in display *	✘	Harmonized System (HS) code	85176200
On Screen Display (OSD)	✘	Master (outer) case width	318 mm
Power		Master (outer) case length	389 mm
Input voltage	100 - 240 V	Master (outer) case height	285 mm
		Products per master (outer) case	6 pc(s)



0065030880121



065030880121

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.