## StarTech.com SV231TDPU34K KVM-kytkin musta

Tuotemerkki : StarTech.com

Tuotekoodi: SV231TDPU34K

Tuotteen nimi : SV231TDPU34K

StarTech.com SV231TDPU34K. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 3840 x 2160 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Kotelon materiaali: Terästä, Keskimääräinen vikaantumisaika: 156000 h. Tulojännite: 100 - 240 V, Syöttöjännite: 1 A, Ulostulojännite: 12 V. Tuotteen leveys: 160 mm, Tuotteen syvyys: 100 mm, Tuotteen korkeus: 98 mm






Ports & interfaces
--------------------

Ports & interfaces		Display	
Number of computers controlled *	2	On Screen Display (OSD)	×
Keyboard port type *	USB	Power	
Mouse port type *	USB	Input voltage	100 - 240 V
Video port type *	DisplayPort	Input current	100 - 240 V 1 A
DisplayPorts quantity	9	Output voltage	1 A 12 V
DisplayPort version	1.2	Output vonage Output current	3 A
Console ports *	3.5mm headphone, DisplayPort, USB A	Power consumption (typical)	36 W
Console USB ports quantity	4	Power plug type	Туре М
USB hub	1	Compatible power plug types	AU, EU, JP, UK, US
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2	Operational conditions	
Audio connections	1	Operating temperature (T-T)	0 - 40 °C
Headphone outputs	3	Storage temperature (T-T)	-10 - 60 °C
DC-in jack	- -	Operating relative humidity (H-H)	0 - 80%
	•	Weight & dimensions	
Performance		Width	160 mm
HD type *	4K Ultra HD	Depth	100 mm
Maximum resolution *	3840 x 2160 pixels	Height	98 mm
Video bandwidth	60 Hz	Weight	850 g
Scan interval	3,8,15,30 s	Packaging data	
HDCP	1	Package width	238 mm
Daisy chain	×	Package depth	189 mm
Audio channels	5.1	Package height	91 mm
Number of displays supported	3		
Design		Packaging content	
Product colour *	Black	Quick installation guide Rubber feet	J J
Housing material	Steel		
LED indicators	1		

Display

Design		Other features	
Push button	✓	IP control	×
Hot keys	✓	Logistics data	
Mean time between failures (MTBF) Certification	156000 h CE, RoHS, FCC	Harmonized System (HS) code	85176200
		Master (outer) case width	397 mm
Display		Master (outer) case length	317 mm
Built-in display *	×	Master (outer) case height	280 mm
		Products per master (outer) case	6 pc(s)





065030881784

0065030881784

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.