

ZYXEL

## Zyxel NWA90AX PRO 2400 Mbit/s White Power over Ethernet (PoE)

**Brand :** Zyxel

**Product code:** NWA90AXPRO-EU0102F

**Product name :** NWA90AX PRO

NWA90AXPRO, 2.5GB LAN Port, 2x2:3x3 MU-MIMO, Standalone / NebulaFlex Wireless Access Point, Single Pack include Power Adaptor, EU and UK, ROHS  
Zyxel NWA90AX PRO. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2400 Mbit/s. Security algorithms: 802.1x RADIUS, EAP, WEP, WPA, WPA2, WPA2-Enterprise, WPA2-PSK, WPA3. Ethernet LAN data rates: 1000,2500 Mbit/s. Power over Ethernet (PoE). Product colour: White



Features		Power	
2.4 GHz *	✓	AC input frequency	50/60 Hz
5 GHz *	✓	Input current	0.3 A
6 GHz *	✗	Output voltage	12 V
Maximum data transfer rate *	2400 Mbit/s	Output current	2 A
Maximum data transfer rate (2.4 GHz)	575 Mbit/s	<b>Design</b>	
Maximum data transfer rate (5 GHz)	2400 Mbit/s	Placement *	Ceiling
Ethernet LAN data rates	1000,2500 Mbit/s	Product colour *	White
Networking standards	IEEE 802.11n, IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g	LED indicators	✓
MIMO	✓	<b>Antenna</b>	
MIMO type	Multi User MIMO	Antenna type *	Internal
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna features	Integrated antenna
VLAN support	✓	Antenna gain level (max)	4 dBi
<b>Security</b>		<b>Weight &amp; dimensions</b>	
Security algorithms *	802.1x RADIUS, EAP, WEP, WPA, WPA2, WPA2-Enterprise, WPA2-PSK, WPA3	Width	140 mm
MAC address filtering	✓	Depth	140 mm
<b>Protocols</b>		Height	37.5 mm
Management protocols	SNMP	Weight	352 g
<b>Management features</b>		<b>Packaging data</b>	
Web-based management	✓	Package width	240 mm
Firmware upgradeable	✓	Package depth	155 mm
<b>Ports &amp; interfaces</b>		Package height	60 mm
Ethernet LAN (RJ-45) ports *	1	Package weight	668 g
		<b>Operational conditions</b>	
		Operating relative humidity (H-H)	10 - 90%
		Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-40 - 70 °C

Ports & interfaces		Operational conditions	
DC-in jack	✓	Storage relative humidity (H-H)	10 - 90%
Power			
Power over Ethernet (PoE) *	✓		
AC input voltage	100 - 240 V		



4718937630592

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date