



DELL P Series 14 Portable Monitor - P1424H

Brand : DELL

Product family: P Series

Product code: DELL-P1424H



Product name : 14 Portable Monitor - P1424H

- 35.6cm (14") Full HD 1920 x 1080 LED IPS

- 6ms, 16:9, 300cd/m², 700:1

- USB

35.6cm (14") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m², 16.7M, 6ms, 178°/178°, 700:1

DELL P Series 14 Portable Monitor - P1424H:

Experience dual-screen productivity anywhere with Dell's 14" portable monitor.

DELL P Series 14 Portable Monitor - P1424H. Display diagonal: 35.6 cm (14"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 6 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Product colour: Grey



Display

| | |
|------------------------------|-----------------------|
| Display diagonal * | 35.6 cm (14") |
| Display resolution * | 1920 x 1080 pixels |
| HD type * | Full HD |
| Native aspect ratio * | 16:9 |
| Display technology * | LCD |
| Panel type * | IPS |
| Backlight type | LED |
| Touchscreen * | ✗ |
| Display brightness (typical) | 300 cd/m ² |
| Response time * | 6 ms |
| Anti-glare screen | ✓ |
| Screen shape * | Flat |
| Contrast ratio (typical) * | 700:1 |
| Maximum refresh rate * | 60 Hz |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| Display number of colours * | 16.7 million colours |
| Pixel pitch | 0.1611 x 0.1611 mm |
| Pixel density | 158 ppi |
| Viewable size, horizontal | 30.9 cm |
| Viewable size, vertical | 17.4 cm |
| Digital horizontal frequency | 30 - 80 kHz |
| Digital vertical frequency | 56 - 61 Hz |
| Display diagonal (metric) | 35.56 cm |
| Colour gamut standard | NTSC |
| Colour gamut | 72% |

Multimedia

Built-in speaker(s) * ✗

Power

| | |
|---|---------------|
| Energy efficiency class (HDR) * | Not available |
| Energy consumption (SDR) per 1000 hours * | 5 kWh |
| Power consumption (typical) * | 5 W |
| Power consumption (standby) * | 0.3 W |
| Power consumption (max) | 7.5 W |
| Power consumption (off) | 0.3 W |
| Power supply type | Internal |
| Energy efficiency scale | A to G |
| European Product Registry for Energy Labelling (EPREL) code | 1435998 |

Operational conditions

| | |
|-----------------------------------|----------------|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| Operating relative humidity (H-H) | 10 - 80% |
| Storage relative humidity (H-H) | 5 - 90% |
| Operating altitude | 0 - 5000 m |
| Non-operating altitude | 5000 - 12192 m |

Weight & dimensions

| | |
|------------------------|----------|
| Width (with stand) | 322.4 mm |
| Depth (with stand) | 14.3 mm |
| Height (with stand) | 202.7 mm |
| Weight (with stand) | 590 g |
| Width (without stand) | 322.4 mm |
| Depth (without stand) | 4.95 mm |
| Height (without stand) | 202.7 mm |
| Bezel width (side) | 6.53 mm |
| Bezel width (top) | 6.54 mm |
| Bezel width (bottom) | 2.22 cm |

| | | | |
|--|----------|---|--------------|
| Multimedia | | Packaging data | |
| Built-in camera * | ✗ | Package weight | 1.12 kg |
| Design | | Sustainability | |
| Market positioning * | Business | Sustainability certificates | ENERGY STAR |
| Product colour * | Grey | Doesn't contain | PVC/BFR |
| Front bezel colour | Black | Carbon footprint | |
| Ports & interfaces | | Total carbon footprint (kg of CO2e) | 421 |
| Number of USB Type-C upstream ports quantity | 2 | Total carbon emissions, standard deviation (kg of CO2e) | 99 |
| USB Type-C DisplayPort Alternate Mode | ✓ | Carbon emissions, manufacturing (kg of CO2e) | 368 |
| USB Power Delivery (USB PD) | ✓ | Carbon emissions, logistics (kg of CO2e) | 6 |
| USB Power Delivery up to | 65 W | Carbon emissions, energy usage (kg of CO2e) | 47 |
| HDMI * | ✗ | Carbon emissions, end-of-life (kg of CO2e) | 1 |
| Headphone out * | ✗ | Total carbon emissions, w/o use phase (kg of CO2e) | 374 |
| HDCP | ✓ | PAIA version | 1.3.2 |
| HDCP version | 1.4 | Other features | |
| Ergonomics | | Heavy metals free | Hg (mercury) |
| VESA mounting * | ✗ | Compliance certificates | RoHS |
| Cable lock slot * | ✗ | | |
| Height adjustment * | ✗ | | |
| Tilt adjustment | ✓ | | |
| Tilt angle range | 10 - 90° | | |
| On Screen Display (OSD) | ✓ | | |
| Plug and Play | ✓ | | |
| LED indicators | ✓ | | |
| Power | | | |
| Energy efficiency class (SDR) * | B | | |



5397184821572

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date