## ASUS PRIME H610M-E D4-CSM Intel H610 LGA 1700 mikro ATX

Tuotemerkki : ASUS Tuotekoodi: 90MB19N0-M1EAYC

Tuotteen nimi: PRIME H610M-E D4-CSM

ASUS PRIME H610M-E D4-CSM. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1700, Yhteensopivat prosessorit: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium®. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 64 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, Tuetut tallennusasematyypit: HDD & SSD. Ethernet-liitännän tyyppi: Gigabitti Ethernet. Komponentti (tuotteelle): PC, Emolevyn muototekijä: mikro ATX, Emolevyn piirisarjan perhe: Intel





Processor		Internal I/O	
Processor manufacturer *	Intel  LGA 1700  Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium®	RGB LED pin header	✓
Processor socket *		Rear panel I/O ports	
Compatible processor series *		USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	2
Maximum number of SMP processors	1	ports quantity * Ethernet LAN (RI-45) ports *	2
Supported processor sockets	LGA 1700	PS/2 ports quantity	2
Memory		VGA (D-Sub) ports quantity *	1
Supported memory types * Number of memory slots * Memory slots type Memory channels ECC compatibility Supported memory clock speeds Supported memory clock speed (max) Maximum internal memory * Unbuffered memory	DDR4-SDRAM 2 DIMM Dual-channel Non-ECC 2133,2400,2666,2800,2933,3000,3200 MHz 3200 MHz 64 GB	Microphone in  Network  Ethernet LAN  Ethernet interface type	1 2.1 1 1.4 1  ✓ Gigabit Ethernet
Storage controllers		Wi-Fi *	×
Supported storage drive types Supported storage drive interfaces Number of HDDs supported Number of storage drives supporte	4	Features  Motherboard chipset *  Audio output channels *  Product colour	Intel H610 7.1 channels Black
Graphics		Component for *	PC
Parallel processing technology support *	Not supported	Motherboard form factor *  Motherboard chipset family *  Cooling type	micro ATX Intel Passive

Internal I/O		Features	
USB 2.0 connectors *	2	Power source type	ATX
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Windows operating systems supported	Windows 10 x64, Windows 11 x64
Number of SATA III connectors *	4	Expansion slots	
S/PDIF out connector	<b>✓</b>	PCI Express x1 (Gen 3.x) slots	1
Front panel audio connector	✓	PCI Express x16 (Gen 4.x) slots	1
ATX Power connector (24-pin)	✓	Number of M.2 (M) slots	2
CPU fan connector	✓	BIOS	
Number of chassis fan connectors	2	BIOS type *	UEFI AMI
EPS power connector (8-pin)	✓	BIOS memory size	128 Mbit
Number of COM connectors	1	Weight & dimensions	
TPM connector	✓	· ·	0.44
12V power connector	✓	Width	244 mm
		Depth	211 mm
		Packaging content	
		Cables included	SATA
		User guide	✓
		Drivers included	✓

