Lindy 70m Cat.6 4 Port HDMI 4K60 Splitter Extender

Brand : Lindy

Product code: 38262

Product name : 70m Cat.6 4 Port HDMI 4K60 Splitter Extender

- Distribute 4K HDMI signals to up to 4 displays in multiple locations

- Supports resolutions up to 4K@60Hz, with additional support for HDR

- Features a loop-through HDMI output on the transmitter for local monitoring or cascading for larger installs

- Supports Power over Cable (PoC) to the receivers, only a single power supply is required for operation - 2 year warranty

70m Cat.6 4 Port HDMI 4K60 Splitter Extender

Lindy 70m Cat.6 4 Port HDMI 4K60 Splitter Extender. Type: AV transmitter & receiver, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat6. Connectivity technology: Wired. Receiver dimensions (WxDxH): 100 x 88 x 23 mm, Receiver weight: 199 g, Transmitter dimensions (WxDxH): 180 x 103 x 23 mm. Package width: 423 mm, Package depth: 60 mm, Package height: 354 mm. Cables included: IR, IR sensor





Features


Type *	AV transmitter & receiver	Remote (
Maximum resolution *	3840 x 2160 pixels	Remote (
Cable types supported	Cat6	DC-in jac
Maximum transfer distance	70 m	Operatio
Chipset	GSV2006, GSV5100	Operating
Maximum refresh rate	60 Hz	
Extended display identification data (EDID)	<	Storage t Operating
Bandwidth	18 Gbit/s	Weight &
Audio formats supported	LPCM	Receiver
HDCP	1	Receiver
Material	Metal	Transmit
HDCP version	2.2	Transmit
Product colour	Black	
Certification	CE, UKCA, FCC, RoHS, REACH &	Packagiı
Ceruncation	California Propositon 65	Package
Ports & interfaces		Package

Ports & interfaces

Connectivity technology *	Wired
RJ-45 input ports	4
RJ-45 output ports	4
HDMI in	1
Number of HDMI outputs	5
HDMI version	2.0

Ports & interfaces	
Remote (IR) input	4
Remote (IR) output	1
DC-in jack	✓
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 80 °C
Operating relative humidity (H-H)	5 - 90%
Weight & dimensions	
Receiver dimensions (WxDxH)	100 x 88 x 23 mm
Receiver weight	199 g
Transmitter dimensions (WxDxH)	180 x 103 x 23 mm
Transmitter weight	390 g
Packaging data	
Package width	423 mm
Package depth	60 mm
Package height	354 mm
Package weight	2 kg
Package type	Box
Packaging content	
Cables included	IR, IR sensor
Manual	✓
Mounting brackets included	✓





4002888382625

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.