



Lindy HDMI over Powerline Extender, Receiver

Brand : Lindy

Product code: 38227

Product name : HDMI over Powerline Extender, Receiver

HDMI over Powerline Extender, Receiver

[Lindy HDMI over Powerline Extender, Receiver:](#)

HDMI over Powerline extenders provide a useful solution for extending HDMI content to one or more displays within one electrical circuit.

The Lindy HDMI over Powerline Receiver is one part of a high-quality solution for extending HDMI content from a source device to a display using a single electrical power circuit. Combined with the compatible transmitter unit, this extender provides simple, hassle-free content distribution within small office, store front or residential setups.

Supporting resolutions up to 1920x1080@60Hz ensuring excellent Full HD quality for the user. This device is ideal for sharing video and audio content into bedrooms, home offices or small-scale digital signage using pre-existing electrical wiring.

Up to 3 compatible receivers can be connected to a single transmitter allowing for larger scale distribution to multiple displays. A 3.5mm IR connection also allows for simple control from the display side of the setup.



Features		Operational conditions	
Type *	AV receiver	Storage temperature (T-T)	-4 - 104 °C
Maximum resolution *	1920 x 1080 pixels	Operating relative humidity (H-H)	20 - 90%
Chipset	ITE	Storage relative humidity (H-H)	20 - 90%
Maximum refresh rate	60 Hz	Weight & dimensions	
Extended display identification data (EDID)	✓	Width	135 mm
LED indicators	✓	Depth	96.5 mm
Bandwidth	6.75 Gbit/s	Height	29 mm
HDCP	✓	Weight	1.06 kg
Material	Metal	Packaging data	
HDCP version	1.4	Quantity per pack	1 pc(s)
Product colour	Black	Package width	268 mm
Certification	CE, FCC, RoHS, REACH	Package depth	150 mm
Ports & interfaces		Package height	80 mm
Connectivity technology *	Wired	Package weight	1.27 kg
Number of HDMI outputs	1	Packaging content	
Remote (IR) input	1	Cables included	AC, IR
Power		Manual	✓
AC input voltage	100-240 V	Technical details	
Operational conditions		Compliance certificates	CE, REACH, RoHS
Operating temperature (T-T)	32 - 104 °C		



4002888382274

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-NOV-2024. Prints or copies of Information are only valid on the printed Publication date