



Lindy 70m C6 HDBaseT HDMI 18G & IR Extender Receiver

Brand : Lindy

Product code: 38214

Product name : 70m C6 HDBaseT HDMI 18G & IR Extender Receiver



- Distributes HDMI resolutions up to 70m over Cat.6 network cable via HDBaseT technology
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- RS-232 and CEC pass-through and bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation

70m Cat.6 HDMI 4K60, IR & RS-232 HDBaseT Receiver with PoC, Receiver

Lindy 70m C6 HDBaseT HDMI 18G & IR Extender Receiver. Type: AV receiver, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat6. USB connector type: Mini-USB B. Operating voltage: 24 V, Input current: 1 A. Width: 157 mm, Depth: 90 mm, Height: 20 mm. Package width: 220 mm, Package depth: 130 mm, Package height: 70 mm



| Features | | Ports & interfaces | |
|---|---|-----------------------------------|-------------|
| Type * | AV receiver | DC-in jack | ✓ |
| Maximum resolution * | 3840 x 2160 pixels | Power | |
| Cable types supported | Cat6 | Operating voltage | 24 V |
| Maximum transfer distance | 70 m | Input current | 1 A |
| Chipset | VS010 | Operational conditions | |
| Extended display identification data (EDID) | ✓ | Operating temperature (T-T) | 0 - 40 °C |
| CEC pass-through | ✓ | Storage temperature (T-T) | -20 - 60 °C |
| LED indicators | ✓ | Operating relative humidity (H-H) | 20 - 90% |
| Bandwidth | 18 Gbit/s | Weight & dimensions | |
| HDCP | ✓ | Width | 157 mm |
| Material | Metal | Depth | 90 mm |
| HDCP version | 2.2 | Height | 20 mm |
| Product colour | Black | Weight | 345 g |
| Certification | CE, FCC, REACH, California Proposition 65 | Packaging data | |
| Ports & interfaces | | Package width | 220 mm |
| RJ-45 input ports | 1 | Package depth | 130 mm |
| Number of HDMI outputs | 1 | Package height | 70 mm |
| USB ports quantity | 1 | Package weight | 847 g |
| USB version | 2.0 | Package type | Box |
| USB connector type | Mini-USB B | Packaging content | |
| RS-232 input ports | 1 | Cables included | AC, IR |
| Remote (IR) input | 1 | Manual | ✓ |
| Remote (IR) output | 1 | Technical details | |
| | | Compliance certificates | RoHS |



4002888382144

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-NOV-2024. Prints or copies of Information are only valid on the printed Publication date