Epson DS-C330 ADF + Sheet-fed scanner 600 x 600 DPI A4 Black, White

Brand: Epson Product code: B11B272401

Product name: DS-C330

DS-C330

Epson DS-C330 ADF + Sheet-fed scanner 600 x 600 DPI A4 Black, White:

Compact deskop scanner

The scanner's U-turn path position allows paper to be scanned without adding to the footprint of the device. Switch to straight path mode to scan passports and booklets up to 5mm thick. Paper protection technology ensures that the original documents remain pristine. Made from up to 30% recycled plastics* and with a low power consumtion, it also has a lower environmental impact.





Scanning		Paper handling	
Maximum scan size * Optical scanning resolution *	215.9 x 3048 mm 600 x 600 DPI	Paper tray media weight	40 - 413 g/m²
		Ports & interfaces	
Duplex scanning *		USB port *	/
Input colour depth	30 bit	USB version	2.0
Output colour depth Output monochrome depth	24 bit 8 bit	Power	
	o Dic	Power supply type *	AC
Design		Power consumption (typical)	10 W
Scanner type *	ADF + Sheet-fed scanner	Power consumption (standby)	1 W
Product colour * Control type	Black, White Buttons	Power consumption (PowerSave)	3.3 W
Built-in display *	X	Input voltage	100 - 240 V
. ,	^	Weight & dimensions	
Performance		Width	296 mm
Light source	ReadyScan LED	Depth	104 mm
Daily duty cycle (max) * Scan to	5000 pages E-mail, FTP, Network folder, Print	Height	125 mm
Scan drivers	ISIS, SANE, WIA	Weight	1.8 kg
	ISIS, SAIVE, WIA	System requirements	
Input capacity Standard input capacity	20 sheets	Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Paper handling			Windows Server 2003, Windows
	Business Card, Plastic Card, Post	Server operating systems supported	Windows Server 2012 x64, Windows
Scanning media types supported	Card(JPN)		
Maximum ISO A-series paper size *	A4		Server 2016
ISO A-series sizes (A0A9)	A4, A5, A6	Operational conditions	
ISO B-series sizes (B0B9)	B5	Operating temperature (T-T)	5 - 35 °C
Letter	✓	Storage temperature (T-T)	-25 - 60 °C
Legal	✓	Operating relative humidity (H-H)	15 - 80%
		Storage relative humidity (H-H)	15 - 85%



8715946718408

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.