

## Epson DS-C490 ADF + arkinsyöttökanneri 600 x 600 DPI A4 musta, Valkoinen

**Tuotemerkki :** Epson

**Tuotekoodi:** B11B271401

**Tuotteen nimi :** DS-C490

Epson DS-C490. Skannauksen enimmäiskoko: 215,9 x 5588 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, Tulon värisyvyys: 30 bittiä. Skannerityyppi: ADF + arkinsyöttökanneri, Tuotteen väri: musta, Valkoinen, Ohjaustyyppi: Painikkeet. Päivittäinen käyttöjako (maks.): 6500 sivua, Valonlähde: ReadyScan LED, Skannaa: Sähköposti, FTP, Network folder, Tulosta. Vakiosyöttökapasiteetti (arkkia): 20 arkkia. Suurin ISO A-luokan paperikoko: A4, Tuetut skannausmediatyytit: Käyntikortti, Muovikortti, Post Card(JPN), ISO A-sarjan koot (A0...A9): A4, A5, A6



<b>Scanning</b>		<b>Paper handling</b>	
Maximum scan size *	215.9 x 5588 mm	Paper tray media weight	40 - 413 g/m <sup>2</sup>
Optical scanning resolution *	600 x 600 DPI	<b>Ports &amp; interfaces</b>	
Duplex scanning *	✓	USB port *	✓
Input colour depth	30 bit	USB version	2.0
Output colour depth	24 bit	<b>Power</b>	
Output monochrome depth	8 bit	Power supply type *	AC
<b>Design</b>		Power consumption (typical)	10 W
Scanner type *	ADF + Sheet-fed scanner	Power consumption (standby)	1 W
Product colour *	Black, White	Power consumption (PowerSave)	4 W
Control type	Buttons	Input voltage	100 - 240 V
Built-in display *	✗	<b>Weight &amp; dimensions</b>	
<b>Performance</b>		Width	296 mm
Light source	ReadyScan LED	Depth	104 mm
Daily duty cycle (max) *	6500 pages	Height	125 mm
Scan to	E-mail, FTP, Network folder, Print	Weight	1.9 kg
Scan drivers	ICA, ISIS, SANE, WIA	<b>System requirements</b>	
<b>Input capacity</b>		Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Standard input capacity	20 sheets	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2012 x64, Windows Server 2016
<b>Paper handling</b>		<b>Operational conditions</b>	
Scanning media types supported	Business Card, Plastic Card, Post Card(JPN)	Operating temperature (T-T)	5 - 35 °C
Maximum ISO A-series paper size *	A4	Storage temperature (T-T)	-25 - 60 °C
ISO A-series sizes (A0...A9)	A4, A5, A6	Operating relative humidity (H-H)	15 - 80%
ISO B-series sizes (B0...B9)	B5, B6	Storage relative humidity (H-H)	15 - 85%
Letter	✓		
Legal	✓		



8715946718293

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-DEC-2024. Prints or copies of Information are only valid on the printed Publication date